

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P771639

Luminaire Tested: LD6D75BD010-EU6DR6570959035-6LBDP1LI

Issue Date: 2/5/2024

Test Information

Test Method: LM-79-2019
Report Number: P771639
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-59)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/5/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD6D75BD010-EU6DR6570959035-6LBDP1LI
Description: 6 INCH ROUND DEEP 45° CUTOFF SPECULAR CLEAR TRIM, WITH 65° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 3500K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 7931.9 lumens
Efficiency: N/A
Efficacy: 109.6 lumens/watt
Spacing Criteria (0/90/45): 0.98 / 0.98 / 0.92
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct


Input Watts (W): 72.4
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



Downlight

TEST NUMBER: P771639
CATALOG NUMBER: LD6D75BD010-EU6DR6570959035-6LBDP1LI

Luminous Intensity Polar Plot





TEST NUMBER: P771639

CATALOG NUMBER: LD6D75BD010-EU6DR6570959035-6LBDP1LI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	113	111	108	106	111	108	106	104	104	103	101	101	99	98	97	96	95	93																			
2	108	103	99	95	106	101	97	94	98	95	92	95	92	90	92	90	88	87																			
3	102	96	91	87	100	94	90	86	92	88	85	89	86	83	87	84	82	80																			
4	97	89	84	79	95	88	83	79	86	82	78	84	80	77	82	79	76	75																			
5	92	83	78	73	90	83	77	73	81	76	72	79	75	72	77	74	71	69																			
6	87	78	72	68	86	77	72	68	76	71	67	74	70	67	73	69	66	65																			
7	83	73	67	63	81	73	67	63	71	66	62	70	66	62	69	65	62	60																			
8	79	69	63	59	77	68	63	59	67	62	58	66	62	58	65	61	58	57																			
9	75	65	59	55	74	65	59	55	64	58	55	63	58	55	62	58	54	53																			
10	71	61	56	52	70	61	55	52	60	55	51	59	55	51	59	54	51	50																			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	853272
5°	853976
10°	884042
15°	885510
20°	815259
25°	694643
30°	531779
35°	375686
40°	221761
45°	90022
50°	32636
55°	18173
60°	10423
65°	5739
70°	6038
75°	4686
80°	4908
85°	4137

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 90022 cd/sqm



TEST NUMBER: P771639

CATALOG NUMBER: LD6D75BD010-EU6DR6570959035-6LBDP1LI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	752.0	9.5
10°-20°	2169.2	27.3
20°-30°	2602.6	32.8
30°-40°	1749.0	22.1
40°-50°	523.6	6.6
50°-60°	92.4	1.2
60°-70°	26.3	0.3
70°-80°	12.9	0.2
80°-90°	4.1	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	5523.7	69.6
0°-40°	7272.7	91.7
0°-60°	7888.7	99.5
0°-90°	7931.9	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	7931.9	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	7810	
5°	7786	752
15°	7828	2169
25°	5762	2603
35°	2817	1749
45°	583	524
55°	95	92
65°	22	26
75°	11	13
85°	3	4
90°	0	



TEST NUMBER: P771639

CATALOG NUMBER: LD6D75BD010-EU6DR6570959035-6LBDP1LI

CANDELA DISTRIBUTION (FULL):

0°	
0°	7809.5
2.5°	7842.8
5°	7786.2
7.5°	7903.9
10°	7968.2
12.5°	7952.7
15°	7828.4
17.5°	7524.3
20°	7011.6
22.5°	6407.9
25°	5762.0
27.5°	5032.9
30°	4215.0
32.5°	3473.6
35°	2816.6
37.5°	2167.4
40°	1554.8
42.5°	1015.5
45°	582.6
47.5°	308.5
50°	192.0
52.5°	133.2
55°	95.4
57.5°	68.8
60°	47.7
62.5°	31.1
65°	22.2
67.5°	20.0
70°	18.9
72.5°	14.4
75°	11.1
77.5°	10.0
80°	7.8
82.5°	5.5
85°	3.3
87.5°	2.2
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)