

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269



Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P771572

Luminaire Tested: LD6D75BD010-EU6DR6070959040-6LBDP1B

Issue Date: 2/5/2024

**Test Information**

Test Method: LM-79-2019  
Report Number: P771572  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-57)  
Test Lab: COOPER LIGHTING SOLUTIONS  
Issue Date: 2/5/2024  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: PORTFOLIO  
Catalog Number: LD6D75BD010-EU6DR6070959040-6LBDP1B  
Description: 6 INCH ROUND DEEP 45° CUTOFF SPECULAR BLACK TRIM, WITH 60° OPTIC  
Light Source: (1) HIGH LUMEN LED 90CRI / 4000K CCT  
Ballast/Driver: -

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 7126.4 lumens  
Efficiency: N/A  
Efficacy: 98.4 lumens/watt  
Spacing Criteria (0/90/45): 0.91 / 0.91 / 0.83  
Luminous Opening: Circular (Dia: 0.35' x H: 0')  
CIE Type: Direct


Input Watts (W): 72.4  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT



Downlight

TEST NUMBER: P771572  
CATALOG NUMBER: LD6D75BD010-EU6DR6070959040-6LBDP1B

### Luminous Intensity Polar Plot





TEST NUMBER: P771572

CATALOG NUMBER: LD6D75BD010-EU6DR6070959040-6LBDP1B

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	113	110	108	105	111	108	106	104	104	102	100	100	99	97	97	96	95	93																			
2	107	102	98	95	105	101	97	94	97	94	92	94	92	90	92	90	88	86																			
3	102	96	90	86	100	94	89	86	91	88	84	89	86	83	87	84	82	80																			
4	97	89	84	80	95	88	83	79	86	82	78	84	80	77	82	79	76	75																			
5	92	84	78	74	91	83	78	74	81	77	73	80	76	72	78	75	72	70																			
6	88	79	73	69	87	78	73	69	77	72	68	75	71	68	74	70	67	66																			
7	84	75	69	65	83	74	68	64	73	68	64	72	67	64	71	67	63	62																			
8	80	71	65	61	79	70	65	61	69	64	60	68	64	60	67	63	60	59																			
9	77	67	61	57	75	67	61	57	66	61	57	65	60	57	64	60	57	55																			
10	73	64	58	54	72	63	58	54	62	58	54	62	57	54	61	57	54	53																			

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	924739
5°	947476
10°	958920
15°	913495
20°	805422
25°	651448
30°	440651
35°	220815
40°	35814
45°	35060
50°	35764
55°	36307
60°	37302
65°	38159
70°	39070
75°	39513
80°	38130
85°	31717

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°  
 Vertical Angle: 75°  
 Luminance: 39513 cd/sqm



TEST NUMBER: P771572

CATALOG NUMBER: LD6D75BD010-EU6DR6070959040-6LBDP1B

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	825.6	11.6
10°-20°	2233.8	31.3
20°-30°	2403.4	33.7
30°-40°	1044.7	14.7
40°-50°	175.5	2.5
50°-60°	170.6	2.4
60°-70°	145.9	2.0
70°-80°	97.6	1.4
80°-90°	29.2	0.4
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	5462.9	76.7
0°-40°	6507.6	91.3
0°-60°	6853.7	96.2
0°-90°	7126.4	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	7126.4	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	8464	
5°	8639	826
15°	8076	2234
25°	5404	2403
35°	1656	1045
45°	227	175
55°	191	171
65°	148	146
75°	94	98
85°	25	29
90°	0	



TEST NUMBER: P771572

CATALOG NUMBER: LD6D75BD010-EU6DR6070959040-6LBDP1B

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	8463.6
2.5°	8701.5
5°	8638.7
7.5°	8658.5
10°	8643.1
12.5°	8464.7
15°	8075.8
17.5°	7553.8
20°	6927.0
22.5°	6256.2
25°	5403.7
27.5°	4322.1
30°	3492.7
32.5°	2691.9
35°	1655.5
37.5°	708.2
40°	251.1
42.5°	231.3
45°	226.9
47.5°	219.2
50°	210.4
52.5°	200.5
55°	190.6
57.5°	180.6
60°	170.7
62.5°	159.7
65°	147.6
67.5°	135.5
70°	122.3
72.5°	107.9
75°	93.6
77.5°	77.1
80°	60.6
82.5°	43.0
85°	25.3
87.5°	8.8
90°	0.0

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report





Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)