

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P771833

Luminaire Tested: LD6D80BD010-EU6DR3070959024-6LBDP1H

Issue Date: 2/2/2024

Test Information

Test Method: LM-79-2019
Report Number: P771833
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-16)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/2/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD6D80BD010-EU6DR3070959024-6LBDP1H
Description: 6 INCH ROUND DEEP 45° CUTOFF SEMI-SPECULAR CLEAR TRIM, WITH 30° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 2400K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 8087.8 lumens
Efficiency: N/A
Efficacy: 102.5 lumens/watt
Spacing Criteria (0/90/45): 0.52 / 0.52 / 0.49
Luminous Opening: Rectangular (W 0.38' x L: 0.38' x H: 0')
CIE Type: Direct

Input Watts (W): 78.9
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight

TEST NUMBER: P771833

CATALOG NUMBER: LD6D80BD010-EU6DR3070959024-6LBDP1H

Luminous Intensity Polar Plot





TEST NUMBER: P771833

CATALOG NUMBER: LD6D80BD010-EU6DR3070959024-6LBDP1H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	115	113	111	109	112	110	109	107	106	105	104	103	102	101	99	99	98	96																			
2	111	107	104	101	109	105	102	100	102	100	98	99	97	96	97	95	94	92																			
3	107	102	98	95	105	101	97	94	98	95	93	96	93	91	94	92	90	89																			
4	103	98	93	90	102	96	93	90	94	91	89	93	90	88	91	89	87	85																			
5	100	94	89	86	98	93	89	86	91	88	85	90	86	84	88	86	83	82																			
6	97	90	85	82	95	89	85	82	88	84	81	87	83	81	85	83	80	79																			
7	94	87	82	79	92	86	82	79	85	81	78	84	81	78	83	80	78	77																			
8	91	84	79	76	90	83	79	76	82	78	76	81	78	75	80	77	75	74																			
9	88	81	76	73	87	80	76	73	80	76	73	79	75	73	78	75	73	72																			
10	85	78	74	71	85	78	74	71	77	73	71	76	73	71	76	73	70	69																			

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	1990588	1990588	1990588
5°	1933442	1931190	1933542
10°	1674653	1662847	1674257
15°	1092626	1086762	1081294
20°	543310	563698	542585
25°	273681	308620	268073
30°	109579	119399	95473
35°	50823	48674	40806
40°	21942	24371	20664
45°	15480	19214	15620
50°	5323	13992	5621
55°	3069	5792	3243
60°	2143	2541	2143
65°	1395	1395	1395
70°	850	582	850
75°	0	384	0
80°	0	0	0
85°	0	0	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 22.5°
 Vertical Angle: 45°
 Luminance: 19214 cd/sqm



TEST NUMBER: P771833

CATALOG NUMBER: LD6D80BD010-EU6DR3070959024-6LBDP1H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	2286.8	28.3
10°-20°	3683.0	45.5
20°-30°	1591.5	19.7
30°-40°	362.7	4.5
40°-50°	124.6	1.5
50°-60°	30.4	0.4
60°-70°	7.9	0.1
70°-80°	0.8	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	7561.3	93.5
0°-40°	7924.1	98.0
0°-60°	8079.0	99.9
0°-90°	8087.8	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	8087.8	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	26006	26006	26006	26006	26006	
5°	25163	25139	25134	25186	25165	2289
15°	13788	13622	13714	13670	13645	3692
25°	3240	3363	3654	3278	3174	1551
35°	544	555	521	517	437	369
45°	143	178	178	178	144	101
55°	23	24	43	26	24	22
65°	8	8	8	8	8	8
75°	0	0	1	0	0	1
85°	0	0	0	0	0	0
90°	0	0	0	0	0	0



TEST NUMBER: P771833

CATALOG NUMBER: LD6D80BD010-EU6DR3070959024-6LBDP1H

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	26006.0	26006.0	26006.0	26006.0	26006.0
2.5°	25833.7	25815.8	25826.0	25838.8	25843.9
5°	25163.3	25139.1	25134.0	25186.3	25164.6
7.5°	23811.2	23776.7	23724.4	23843.1	23954.2
10°	21546.1	21507.8	21394.2	21450.4	21541.0
12.5°	18202.2	18078.3	18075.8	18254.5	18230.3
15°	13788.2	13622.3	13714.2	13669.5	13645.2
17.5°	9272.2	9208.3	9330.9	9293.9	9134.3
20°	6670.0	6686.6	6920.3	6802.8	6661.1
22.5°	4867.2	4927.2	5204.3	4901.7	4790.6
25°	3240.5	3363.1	3654.2	3277.6	3174.1
27.5°	1993.1	2049.3	2344.2	1967.6	1911.4
30°	1239.8	1211.7	1350.9	1159.3	1080.2
32.5°	813.3	777.6	822.3	738.0	674.2
35°	543.9	555.4	520.9	517.1	436.7
37.5°	339.6	390.7	344.7	367.7	280.9
40°	219.6	283.5	243.9	269.4	206.8
42.5°	180.0	218.3	200.5	213.2	183.9
45°	143.0	177.5	177.5	177.5	144.3
47.5°	79.2	118.7	151.9	121.3	84.3
50°	44.7	60.0	117.5	62.6	47.2
52.5°	30.6	34.5	80.4	35.8	31.9
55°	23.0	24.3	43.4	25.5	24.3
57.5°	17.9	19.2	23.0	19.2	17.9
60°	14.0	14.0	16.6	15.3	14.0
62.5°	10.2	10.2	11.5	10.2	10.2
65°	7.7	7.7	7.7	7.7	7.7
67.5°	3.8	5.1	5.1	5.1	5.1
70°	3.8	2.6	2.6	2.6	3.8
72.5°	2.6	1.3	1.3	1.3	1.3
75°	0.0	0.0	1.3	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report





— 0°-180° - - 45°-225° - - - - 90°-270°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)