

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P772391

Luminaire Tested: LD6D80BD010-EU6DR6570959027-6LBDP1B

Issue Date: 2/5/2024

Test Information

Test Method: LM-79-2019
Report Number: P772391
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-59)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/5/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD6D80BD010-EU6DR6570959027-6LBDP1B
Description: 6 INCH ROUND DEEP 45° CUTOFF SPECULAR BLACK TRIM, WITH 65° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 2700K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 6123.6 lumens
Efficiency: N/A
Efficacy: 77.6 lumens/watt
Spacing Criteria (0/90/45): 0.98 / 0.98 / 0.92
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct


Input Watts (W): 78.9
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



Downlight

TEST NUMBER: P772391
CATALOG NUMBER: LD6D80BD010-EU6DR6570959027-6LBDP1B

Luminous Intensity Polar Plot





TEST NUMBER: P772391

CATALOG NUMBER: LD6D80BD010-EU6DR6570959027-6LBDP1B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10		0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100		
1	113	111	108	106	111	108	106	104	104	103	101	101	99	98	97	96	95	93		
2	108	103	99	95	106	101	97	94	98	95	92	95	92	90	92	90	88	87		
3	102	96	91	87	100	94	90	86	92	88	85	89	86	83	87	84	82	80		
4	97	89	84	79	95	88	83	79	86	82	78	84	80	77	82	79	76	75		
5	92	83	78	73	90	83	77	73	81	76	72	79	75	72	77	74	71	69		
6	87	78	72	68	86	77	72	68	76	71	67	74	70	67	73	69	66	65		
7	83	73	67	63	81	73	67	63	71	66	62	70	66	62	69	65	62	60		
8	79	69	63	59	77	68	63	59	67	62	58	66	62	58	65	61	58	57		
9	75	65	59	55	74	65	59	55	64	58	55	63	58	55	62	58	54	53		
10	71	61	56	52	70	61	55	52	60	55	51	59	55	51	59	54	51	50		

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	658744
5°	659286
10°	682497
15°	683633
20°	629397
25°	536281
30°	410536
35°	290041
40°	171199
45°	69502
50°	25191
55°	14039
60°	8042
65°	4421
70°	4664
75°	3630
80°	3775
85°	3259

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 69502 cd/sqm



TEST NUMBER: P772391

CATALOG NUMBER: LD6D80BD010-EU6DR6570959027-6LBDP1B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	580.5	9.5
10°-20°	1674.6	27.3
20°-30°	2009.2	32.8
30°-40°	1350.3	22.1
40°-50°	404.2	6.6
50°-60°	71.3	1.2
60°-70°	20.3	0.3
70°-80°	9.9	0.2
80°-90°	3.2	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	4264.4	69.6
0°-40°	5614.7	91.7
0°-60°	6090.2	99.5
0°-90°	6123.6	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	6123.6	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	6029	
5°	6011	581
15°	6044	1675
25°	4448	2009
35°	2174	1350
45°	450	404
55°	74	71
65°	17	20
75°	9	10
85°	3	3
90°	0	



TEST NUMBER: P772391

CATALOG NUMBER: LD6D80BD010-EU6DR6570959027-6LBDP1B

CANDELA DISTRIBUTION (FULL):

0°	
0°	6029.1
2.5°	6054.8
5°	6011.1
7.5°	6101.9
10°	6151.6
12.5°	6139.6
15°	6043.7
17.5°	5808.9
20°	5413.1
22.5°	4947.0
25°	4448.4
27.5°	3885.5
30°	3254.0
32.5°	2681.7
35°	2174.5
37.5°	1673.3
40°	1200.3
42.5°	783.9
45°	449.8
47.5°	238.2
50°	148.2
52.5°	102.8
55°	73.7
57.5°	53.1
60°	36.8
62.5°	24.0
65°	17.1
67.5°	15.4
70°	14.6
72.5°	11.1
75°	8.6
77.5°	7.7
80°	6.0
82.5°	4.3
85°	2.6
87.5°	1.7
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)