

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P772393

Luminaire Tested: LD6D80BD010-EU6DR6570959027-6LBDP1LI

Issue Date: 2/5/2024

Test Information

Test Method: LM-79-2019
Report Number: P772393
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-59)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/5/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD6D80BD010-EU6DR6570959027-6LBDP1LI
Description: 6 INCH ROUND DEEP 45° CUTOFF SPECULAR CLEAR TRIM, WITH 65° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 2700K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 8631.8 lumens
Efficiency: N/A
Efficacy: 109.4 lumens/watt
Spacing Criteria (0/90/45): 0.98 / 0.98 / 0.92
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct


Input Watts (W): 78.9
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



Downlight

TEST NUMBER: P772393
CATALOG NUMBER: LD6D80BD010-EU6DR6570959027-6LBDP1LI

Luminous Intensity Polar Plot





TEST NUMBER: P772393
 CATALOG NUMBER: LD6D80BD010-EU6DR6570959027-6LBDP1LI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10		0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100		
1	113	111	108	106	111	108	106	104	104	103	101	101	99	98	97	96	95	93		
2	108	103	99	95	106	101	97	94	98	95	92	95	92	90	92	90	88	87		
3	102	96	91	87	100	94	90	86	92	88	85	89	86	83	87	84	82	80		
4	97	89	84	79	95	88	83	79	86	82	78	84	80	77	82	79	76	75		
5	92	83	78	73	90	83	77	73	81	76	72	79	75	72	77	74	71	69		
6	87	78	72	68	86	77	72	68	76	71	67	74	70	67	73	69	66	65		
7	83	73	67	63	81	73	67	63	71	66	62	70	66	62	69	65	62	60		
8	79	69	63	59	77	68	63	59	67	62	58	66	62	58	65	61	58	57		
9	75	65	59	55	74	65	59	55	64	58	55	63	58	55	62	58	54	53		
10	71	61	56	52	70	61	55	52	60	55	51	59	55	51	59	54	51	50		

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	928563
5°	929336
10°	962048
15°	963650
20°	887197
25°	755934
30°	578699
35°	408845
40°	241330
45°	97964
50°	35509
55°	19792
60°	11341
65°	6256
70°	6549
75°	5108
80°	5348
85°	4513

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 97964 cd/sqm



TEST NUMBER: P772393

CATALOG NUMBER: LD6D80BD010-EU6DR6570959027-6LBDP1LI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	818.3	9.5
10°-20°	2360.6	27.3
20°-30°	2832.2	32.8
30°-40°	1903.3	22.1
40°-50°	569.8	6.6
50°-60°	100.6	1.2
60°-70°	28.6	0.3
70°-80°	14.0	0.2
80°-90°	4.4	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	6011.1	69.6
0°-40°	7914.5	91.7
0°-60°	8584.8	99.5
0°-90°	8631.8	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	8631.8	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	8499	
5°	8473	818
15°	8519	2361
25°	6270	2832
35°	3065	1903
45°	634	570
55°	104	101
65°	24	29
75°	12	14
85°	4	4
90°	0	



TEST NUMBER: P772393

CATALOG NUMBER: LD6D80BD010-EU6DR6570959027-6LBDP1LI

CANDELA DISTRIBUTION (FULL):

0°	
0°	8498.6
2.5°	8534.9
5°	8473.3
7.5°	8601.3
10°	8671.3
12.5°	8654.4
15°	8519.2
17.5°	8188.3
20°	7630.3
22.5°	6973.3
25°	6270.4
27.5°	5477.0
30°	4586.9
32.5°	3780.1
35°	3065.2
37.5°	2358.7
40°	1692.0
42.5°	1105.1
45°	634.0
47.5°	335.7
50°	208.9
52.5°	144.9
55°	103.9
57.5°	74.9
60°	51.9
62.5°	33.8
65°	24.2
67.5°	21.7
70°	20.5
72.5°	15.7
75°	12.1
77.5°	10.9
80°	8.5
82.5°	6.0
85°	3.6
87.5°	2.4
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)