

Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P773914

Luminaire Tested: LD6D90BD010-EU6DR6070959040-6LBDP1LI

Issue Date: 2/5/2024

**Test Information**

Test Method: LM-79-2019  
Report Number: P773914  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-57)  
Test Lab: COOPER LIGHTING SOLUTIONS  
Issue Date: 2/5/2024  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: PORTFOLIO  
Catalog Number: LD6D90BD010-EU6DR6070959040-6LBDP1LI  
Description: 6 INCH ROUND DEEP 45° CUTOFF SPECULAR CLEAR TRIM, WITH 60° OPTIC  
Light Source: (1) HIGH LUMEN LED 90CRI / 4000K CCT  
Ballast/Driver: -

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 12158.0 lumens  
Efficiency: N/A  
Efficacy: 122.9 lumens/watt  
Spacing Criteria (0/90/45): 0.91 / 0.91 / 0.83  
Luminous Opening: Circular (Dia: 0.35' x H: 0')  
CIE Type: Direct


Input Watts (W): 98.9  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT



Downlight

TEST NUMBER: P773914  
CATALOG NUMBER: LD6D90BD010-EU6DR6070959040-6LBDP1LI

### Luminous Intensity Polar Plot





TEST NUMBER: P773914

CATALOG NUMBER: LD6D90BD010-EU6DR6070959040-6LBDP1LI

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	113	110	108	105	111	108	106	104	104	102	100	100	99	97	97	96	95	93																			
2	107	102	98	95	105	101	97	94	97	94	92	94	92	90	92	90	88	86																			
3	102	96	90	86	100	94	89	86	91	88	84	89	86	83	87	84	82	80																			
4	97	89	84	80	95	88	83	79	86	82	78	84	80	77	82	79	76	75																			
5	92	84	78	74	91	83	78	74	81	77	73	80	76	72	78	75	72	70																			
6	88	79	73	69	87	78	73	69	77	72	68	75	71	68	74	70	67	66																			
7	84	75	69	65	83	74	68	64	73	68	64	72	67	64	71	67	63	62																			
8	80	71	65	61	79	70	65	61	69	64	60	68	64	60	67	63	60	59																			
9	77	67	61	57	75	67	61	57	66	61	57	65	60	57	64	60	57	55																			
10	73	64	58	54	72	63	58	54	62	58	54	62	57	54	61	57	54	53																			

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	1577638
5°	1616436
10°	1635958
15°	1558477
20°	1374089
25°	1111405
30°	751770
35°	376713
40°	61103
45°	59814
50°	61006
55°	61928
60°	63655
65°	65099
70°	66639
75°	67418
80°	65060
85°	54157

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°  
 Vertical Angle: 75°  
 Luminance: 67418 cd/sqm



TEST NUMBER: P773914

CATALOG NUMBER: LD6D90BD010-EU6DR6070959040-6LBDP1LI

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	1408.6	11.6
10°-20°	3811.0	31.3
20°-30°	4100.3	33.7
30°-40°	1782.3	14.7
40°-50°	299.3	2.5
50°-60°	291.1	2.4
60°-70°	249.0	2.0
70°-80°	166.6	1.4
80°-90°	49.8	0.4
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	9319.9	76.7
0°-40°	11102.2	91.3
0°-60°	11692.7	96.2
0°-90°	12158.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	12158.0	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	14439	
5°	14738	###
15°	13778	3811
25°	9219	4100
35°	2824	1782
45°	387	299
55°	325	291
65°	252	249
75°	160	167
85°	43	50
90°	0	



TEST NUMBER: P773914

CATALOG NUMBER: LD6D90BD010-EU6DR6070959040-6LBDP1LI

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	14439.2
2.5°	14845.1
5°	14738.0
7.5°	14771.8
10°	14745.5
12.5°	14441.1
15°	13777.8
17.5°	12887.1
20°	11817.8
22.5°	10673.5
25°	9219.0
27.5°	7373.7
30°	5958.7
32.5°	4592.6
35°	2824.3
37.5°	1208.3
40°	428.4
42.5°	394.6
45°	387.1
47.5°	373.9
50°	358.9
52.5°	342.0
55°	325.1
57.5°	308.2
60°	291.3
62.5°	272.5
65°	251.8
67.5°	231.1
70°	208.6
72.5°	184.2
75°	159.7
77.5°	131.5
80°	103.4
82.5°	73.3
85°	43.2
87.5°	15.0
90°	0.0

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report





Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)