

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269



Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P773995

Luminaire Tested: LD6D90BD010-EU6DR6570959040-6LBS1H

Issue Date: 2/2/2024

**Test Information**

Test Method: LM-79-2019  
Report Number: P773995  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-147)  
Test Lab: COOPER LIGHTING SOLUTIONS  
Issue Date: 2/2/2024  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: PORTFOLIO  
Catalog Number: LD6D90BD010-EU6DR6570959040-6LBS1H  
Description: 6 INCH ROUND SHALLOW SEMI-SPECULAR CLEAR TRIM, WITH 65° OPTIC  
Light Source: (1) HIGH LUMEN LED 90CRI / 4000K CCT  
Ballast/Driver: -

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 10650.0 lumens  
Efficiency: N/A  
Efficacy: 107.7 lumens/watt  
Spacing Criteria (0/90/45): 0.95 / 0.95 / 0.96  
Luminous Opening: Circular (Dia: 0.48' x H: 0')  
CIE Type: Direct

Input Watts (W): 98.9  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT




Downlight

TEST NUMBER: P773995

CATALOG NUMBER: LD6D90BD010-EU6DR6570959040-6LBS1H

### Luminous Intensity Polar Plot





TEST NUMBER: P773995

CATALOG NUMBER: LD6D90BD010-EU6DR6570959040-6LBS1H

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	113	110	107	105	111	108	105	103	104	102	100	100	99	97	97	95	94	93																			
2	107	102	97	94	105	100	96	92	97	93	90	94	91	88	91	89	87	85																			
3	101	94	88	84	99	92	87	83	90	86	82	87	84	81	85	82	80	78																			
4	95	87	81	76	93	86	80	76	84	79	75	82	77	74	80	76	73	72																			
5	90	81	74	70	88	80	74	69	78	73	69	76	72	68	75	71	68	66																			
6	85	75	69	64	83	74	68	64	73	67	63	71	67	63	70	66	62	61																			
7	80	70	64	59	79	69	63	59	68	63	59	67	62	58	66	61	58	56																			
8	76	66	59	55	75	65	59	55	64	58	54	63	58	54	62	57	54	52																			
9	72	61	55	51	71	61	55	51	60	54	51	59	54	50	58	54	50	49																			
10	68	58	52	47	67	57	51	47	57	51	47	56	51	47	55	50	47	46																			

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	564760
5°	563335
10°	562850
15°	545501
20°	496614
25°	432764
30°	359942
35°	285199
40°	205843
45°	130047
50°	67782
55°	36025
60°	18923
65°	10406
70°	4371
75°	4806
80°	3330
85°	2881

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°  
 Vertical Angle: 45°  
 Luminance: 130047 cd/sqm



TEST NUMBER: P773995

CATALOG NUMBER: LD6D90BD010-EU6DR6570959040-6LBS1H

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	914.5	8.6
10°-20°	2504.2	23.5
20°-30°	3060.9	28.7
30°-40°	2483.6	23.3
40°-50°	1237.6	11.6
50°-60°	345.2	3.2
60°-70°	78.5	0.7
70°-80°	20.4	0.2
80°-90°	5.2	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	6479.5	60.8
0°-40°	8963.1	84.2
0°-60°	10545.9	99.0
0°-90°	10650.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	10650.0	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	9670	
5°	9609	914
15°	9022	2504
25°	6716	3061
35°	4000	2484
45°	1574	1238
55°	354	345
65°	75	78
75°	21	20
85°	4	5
90°	0	



TEST NUMBER: P773995

CATALOG NUMBER: LD6D90BD010-EU6DR6570959040-6LBS1H

**CANDELA DISTRIBUTION (FULL):**

0°	
0°	9669.9
2.5°	9662.8
5°	9608.8
7.5°	9577.5
10°	9490.8
12.5°	9314.6
15°	9021.9
17.5°	8564.4
20°	7990.3
22.5°	7370.7
25°	6715.6
27.5°	6015.1
30°	5337.3
32.5°	4668.0
35°	4000.1
37.5°	3333.7
40°	2699.9
42.5°	2105.9
45°	1574.5
47.5°	1097.0
50°	746.0
52.5°	514.4
55°	353.8
57.5°	238.7
60°	162.0
62.5°	112.3
65°	75.3
67.5°	38.4
70°	25.6
72.5°	24.2
75°	21.3
77.5°	14.2
80°	9.9
82.5°	7.1
85°	4.3
87.5°	2.8
90°	0.0

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report





Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)