

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P757482

Luminaire Tested: LD6D02D010-EU6DR500210IC9035-6LBSQW1MW

Issue Date: 2/2/2024

Test Information

Test Method: LM-79-2019
Report Number: P757482
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-44)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/2/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD6D02D010-EU6DR500210IC9035-6LBSQW1MW
Description: 6 INCH SQAURE DEEP 45° CUTOFF MATTE WHITE TRIM, WITH 50° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 3500K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 367.3 lumens
Efficiency: N/A
Efficacy: 72.0 lumens/watt
Spacing Criteria (0/90/45): 0.8 / 0.8 / 0.73
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 5.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight



TEST NUMBER: P757482
CATALOG NUMBER: LD6D02D010-EU6DR500210IC9035-6LBSQW1MW

Luminous Intensity Polar Plot





TEST NUMBER: P757482

CATALOG NUMBER: LD6D02D010-EU6DR500210IC9035-6LBSQW1MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20					
RC	80					70					50					30					10					0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0		
RCR	0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	102	102	102	102	102	100		
	1	114	112	109	107	112	110	108	106	106	104	102	102	101	99	98	97	97	97	97	97	97	97	95		
	2	109	105	101	98	107	103	100	97	100	98	95	97	95	93	95	93	91	91	91	91	91	91	90		
	3	105	99	95	91	103	98	94	90	95	92	89	93	90	88	91	88	86	86	86	86	86	86	85		
	4	100	94	89	85	99	93	88	85	90	87	84	89	85	83	87	84	82	82	82	82	82	82	80		
	5	96	89	84	80	95	88	83	79	86	82	79	85	81	78	83	80	77	77	77	77	77	77	76		
	6	92	84	79	75	91	83	79	75	82	78	74	81	77	74	79	76	74	74	74	74	74	74	72		
	7	88	80	75	71	87	79	74	71	78	74	71	77	73	70	76	73	70	70	70	70	70	70	69		
	8	85	76	71	67	84	76	71	67	75	70	67	74	70	67	73	69	66	66	66	66	66	66	65		
	9	81	73	68	64	80	72	67	64	71	67	64	71	67	64	70	66	63	63	63	63	63	63	62		
	10	78	70	64	61	77	69	64	61	68	64	61	68	64	61	67	63	60	60	60	60	60	60	59		

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	64650
5°	63975
10°	62929
15°	57293
20°	47684
25°	33840
30°	17915
35°	7296
40°	2710
45°	1236
50°	510
55°	267
60°	131
65°	52
70°	0
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 1236 cd/sqm



TEST NUMBER: P757482

CATALOG NUMBER: LD6D02D010-EU6DR500210IC9035-6LBSQW1MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	55.1	15.0
10°-20°	139.3	37.9
20°-30°	125.2	34.1
30°-40°	39.2	10.7
40°-50°	6.9	1.9
50°-60°	1.4	0.4
60°-70°	0.2	0.1
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	319.6	87.0
0°-40°	358.8	97.7
0°-60°	367.1	99.9
0°-90°	367.3	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	367.3	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	592	
5°	583	55
15°	506	139
25°	281	125
35°	55	39
45°	8	7
55°	1	1
65°	0	0
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P757482

CATALOG NUMBER: LD6D02D010-EU6DR500210IC9035-6LBSQW1MW

CANDELA DISTRIBUTION (FULL):

	0°
0°	591.7
2.5°	588.8
5°	583.3
7.5°	575.0
10°	567.2
12.5°	542.2
15°	506.5
17.5°	461.2
20°	410.1
22.5°	350.8
25°	280.7
27.5°	206.4
30°	142.0
32.5°	92.5
35°	54.7
37.5°	31.5
40°	19.0
42.5°	12.4
45°	8.0
47.5°	4.9
50°	3.0
52.5°	2.1
55°	1.4
57.5°	1.0
60°	0.6
62.5°	0.3
65°	0.2
67.5°	0.1
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)