

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P766943

Luminaire Tested: LD6D45BD010-EU6DR6540509030-6LBCSSQMW

Issue Date: 2/2/2024

Test Information

Test Method: LM-79-2019
Report Number: P766943
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-147)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/2/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD6D45BD010-EU6DR6540509030-6LBCSSQMW
Description: 6 INCH SQAURE SHALLOW CAST MATTE WHITE TRIM, WITH 65° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 3000K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 4395.6 lumens
Efficiency: N/A
Efficacy: 113.6 lumens/watt
Spacing Criteria (0/90/45): 0.95 / 0.95 / 0.96
Luminous Opening: Circular (Dia: 0.48' x H: 0')
CIE Type: Direct


Input Watts (W): 38.7
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



TEST NUMBER: P766943

CATALOG NUMBER: LD6D45BD010-EU6DR6540509030-6LBCSSQMW

Luminous Intensity Polar Plot





TEST NUMBER: P766943

CATALOG NUMBER: LD6D45BD010-EU6DR6540509030-6LBCSSQMW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

| | | | | | | | | | | | | | | | | | | | | |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|--|-----|-----|-----|--|-----|-----|-----|-----|
| RF | 20 | | | | 20 | | | | 20 | | | | 20 | | | | 20 | | | |
| RC | 80 | | | | 70 | | | | 50 | | | | 30 | | | | 10 | 0 | | |
| RW | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 50 | 30 | 10 | | 50 | 30 | 10 | | 50 | 30 | 10 | 0 |
| RCR | | | | | | | | | | | | | | | | | | | | |
| 0 | 119 | 119 | 119 | 119 | 116 | 116 | 116 | 116 | 111 | 111 | 111 | | 106 | 106 | 106 | | 102 | 102 | 102 | 100 |
| 1 | 113 | 110 | 107 | 105 | 111 | 108 | 105 | 103 | 104 | 102 | 100 | | 100 | 99 | 97 | | 97 | 95 | 94 | 93 |
| 2 | 107 | 102 | 97 | 94 | 105 | 100 | 96 | 92 | 97 | 93 | 90 | | 94 | 91 | 88 | | 91 | 89 | 87 | 85 |
| 3 | 101 | 94 | 88 | 84 | 99 | 92 | 87 | 83 | 90 | 86 | 82 | | 87 | 84 | 81 | | 85 | 82 | 80 | 78 |
| 4 | 95 | 87 | 81 | 76 | 93 | 86 | 80 | 76 | 84 | 79 | 75 | | 82 | 77 | 74 | | 80 | 76 | 73 | 72 |
| 5 | 90 | 81 | 74 | 70 | 88 | 80 | 74 | 69 | 78 | 73 | 69 | | 76 | 72 | 68 | | 75 | 71 | 68 | 66 |
| 6 | 85 | 75 | 69 | 64 | 83 | 74 | 68 | 64 | 73 | 67 | 63 | | 71 | 67 | 63 | | 70 | 66 | 62 | 61 |
| 7 | 80 | 70 | 64 | 59 | 79 | 69 | 63 | 59 | 68 | 63 | 59 | | 67 | 62 | 58 | | 66 | 61 | 58 | 56 |
| 8 | 76 | 66 | 59 | 55 | 75 | 65 | 59 | 55 | 64 | 58 | 54 | | 63 | 58 | 54 | | 62 | 57 | 54 | 52 |
| 9 | 72 | 61 | 55 | 51 | 71 | 61 | 55 | 51 | 60 | 54 | 51 | | 59 | 54 | 50 | | 58 | 54 | 50 | 49 |
| 10 | 68 | 58 | 52 | 47 | 67 | 57 | 51 | 47 | 57 | 51 | 47 | | 56 | 51 | 47 | | 55 | 50 | 47 | 46 |

AVERAGE LUMINANCE (cd/sqm):

| | |
|-----|--------|
| | 0° |
| 0° | 233096 |
| 5° | 232509 |
| 10° | 232309 |
| 15° | 225150 |
| 20° | 204971 |
| 25° | 178619 |
| 30° | 148561 |
| 35° | 117713 |
| 40° | 84955 |
| 45° | 53671 |
| 50° | 27976 |
| 55° | 14866 |
| 60° | 7814 |
| 65° | 4298 |
| 70° | 1810 |
| 75° | 1986 |
| 80° | 1379 |
| 85° | 1206 |

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 53671 cd/sqm



TEST NUMBER: P766943

CATALOG NUMBER: LD6D45BD010-EU6DR6540509030-6LBCSSQMW

ZONAL LUMENS:

| Zone | Lumens | % Fixture |
|-----------|--------|-----------|
| 0°-10° | 377.4 | 8.6 |
| 10°-20° | 1033.6 | 23.5 |
| 20°-30° | 1263.4 | 28.7 |
| 30°-40° | 1025.0 | 23.3 |
| 40°-50° | 510.8 | 11.6 |
| 50°-60° | 142.5 | 3.2 |
| 60°-70° | 32.4 | 0.7 |
| 70°-80° | 8.4 | 0.2 |
| 80°-90° | 2.2 | 0.0 |
| 90°-100° | 0.0 | 0.0 |
| 100°-110° | 0.0 | 0.0 |
| 110°-120° | 0.0 | 0.0 |
| 120°-130° | 0.0 | 0.0 |
| 130°-140° | 0.0 | 0.0 |
| 140°-150° | 0.0 | 0.0 |
| 150°-160° | 0.0 | 0.0 |
| 160°-170° | 0.0 | 0.0 |
| 170°-180° | 0.0 | 0.0 |
| 0°-30° | 2674.3 | 60.8 |
| 0°-40° | 3699.4 | 84.2 |
| 0°-60° | 4352.6 | 99.0 |
| 0°-90° | 4395.6 | 100.0 |
| 90°-120° | 0.0 | 0.0 |
| 90°-150° | 0.0 | 0.0 |
| 90°-180° | 0.0 | 0.0 |
| 0°-180° | 4395.6 | 100.0 |

CANDELA DISTRIBUTION:

| | 0° | Flux |
|-----|------|------|
| 0° | 3991 | |
| 5° | 3966 | 377 |
| 15° | 3724 | 1034 |
| 25° | 2772 | 1263 |
| 35° | 1651 | 1025 |
| 45° | 650 | 511 |
| 55° | 146 | 142 |
| 65° | 31 | 32 |
| 75° | 9 | 8 |
| 85° | 2 | 2 |
| 90° | 0 | |



TEST NUMBER: P766943

CATALOG NUMBER: LD6D45BD010-EU6DR6540509030-6LBCSSQMW

CANDELA DISTRIBUTION (FULL):

| | 0° |
|-------|--------|
| 0° | 3991.1 |
| 2.5° | 3988.2 |
| 5° | 3965.9 |
| 7.5° | 3953.0 |
| 10° | 3917.2 |
| 12.5° | 3844.5 |
| 15° | 3723.7 |
| 17.5° | 3534.8 |
| 20° | 3297.9 |
| 22.5° | 3042.2 |
| 25° | 2771.8 |
| 27.5° | 2482.6 |
| 30° | 2202.9 |
| 32.5° | 1926.6 |
| 35° | 1651.0 |
| 37.5° | 1375.9 |
| 40° | 1114.3 |
| 42.5° | 869.2 |
| 45° | 649.8 |
| 47.5° | 452.8 |
| 50° | 307.9 |
| 52.5° | 212.3 |
| 55° | 146.0 |
| 57.5° | 98.5 |
| 60° | 66.9 |
| 62.5° | 46.3 |
| 65° | 31.1 |
| 67.5° | 15.8 |
| 70° | 10.6 |
| 72.5° | 10.0 |
| 75° | 8.8 |
| 77.5° | 5.9 |
| 80° | 4.1 |
| 82.5° | 2.9 |
| 85° | 1.8 |
| 87.5° | 1.2 |
| 90° | 0.0 |

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)