

Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P767785

Luminaire Tested: LD6D50D010-EU6DR7040509024-6LBSQW1MW

Issue Date: 2/5/2024

**Test Information**

Test Method: LM-79-2019  
Report Number: P767785  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-73)  
Test Lab: COOPER LIGHTING SOLUTIONS  
Issue Date: 2/5/2024  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: PORTFOLIO  
Catalog Number: LD6D50D010-EU6DR7040509024-6LBSQW1MW  
Description: 6 INCH SQAURE DEEP 45° CUTOFF MATTE WHITE TRIM, WITH 70° OPTIC  
Light Source: (1) HIGH LUMEN LED 90CRI / 2400K CCT  
Ballast/Driver: -

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 4097.9 lumens  
Efficiency: N/A  
Efficacy: 87.2 lumens/watt  
Spacing Criteria (0/90/45): 0.88 / 0.88 / 0.82  
Luminous Opening: Circular (Dia: 0.35' x H: 0')  
CIE Type: Direct


Input Watts (W): 47  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT



TEST NUMBER: P767785

CATALOG NUMBER: LD6D50D010-EU6DR7040509024-6LBSQW1MW

### Luminous Intensity Polar Plot





TEST NUMBER: P767785

CATALOG NUMBER: LD6D50D010-EU6DR7040509024-6LBSQW1MW

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	112	109	106	103	110	107	104	102	103	101	99	99	97	96	95	94	93	91																			
2	106	100	95	91	103	98	94	90	95	91	88	92	89	86	89	87	85	83																			
3	100	92	87	82	98	91	86	81	88	84	80	86	82	79	83	80	78	76																			
4	94	86	80	75	92	85	79	74	82	77	73	80	76	73	78	75	72	70																			
5	89	80	74	69	87	79	73	69	77	72	68	75	71	67	74	70	67	65																			
6	85	75	68	64	83	74	68	64	73	67	63	71	66	63	70	66	62	61																			
7	80	70	64	59	79	70	64	59	68	63	59	67	62	59	66	62	58	57																			
8	77	66	60	56	75	66	60	56	65	59	55	64	59	55	63	58	55	53																			
9	73	63	57	52	72	62	56	52	61	56	52	60	55	52	60	55	52	50																			
10	70	59	53	49	69	59	53	49	58	53	49	57	52	49	57	52	49	48																			

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	503397
5°	488430
10°	474817
15°	468590
20°	437570
25°	328720
30°	232380
35°	82310
40°	43288
45°	46093
50°	47730
55°	48632
60°	48927
65°	47906
70°	45203
75°	41877
80°	37186
85°	30212

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°  
 Vertical Angle: 57.5°  
 Luminance: 48947 cd/sqm



TEST NUMBER: P767785

CATALOG NUMBER: LD6D50D010-EU6DR7040509024-6LBSQW1MW

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	420.0	10.3
10°-20°	1152.2	28.1
20°-30°	1269.0	31.0
30°-40°	484.8	11.8
40°-50°	228.9	5.6
50°-60°	227.6	5.6
60°-70°	182.2	4.4
70°-80°	104.7	2.6
80°-90°	28.5	0.7
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2841.2	69.3
0°-40°	3326.0	81.2
0°-60°	3782.5	92.3
0°-90°	4097.9	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	4097.9	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	4607	
5°	4453	420
15°	4143	1152
25°	2727	1269
35°	617	485
45°	298	229
55°	255	228
65°	185	182
75°	99	105
85°	24	28
90°	0	



TEST NUMBER: P767785

CATALOG NUMBER: LD6D50D010-EU6DR7040509024-6LBSQW1MW

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	4607.3
2.5°	4559.1
5°	4453.3
7.5°	4365.1
10°	4279.7
12.5°	4207.5
15°	4142.6
17.5°	3985.8
20°	3763.3
22.5°	3283.3
25°	2726.7
27.5°	2373.7
30°	1841.9
32.5°	1189.7
35°	617.1
37.5°	333.4
40°	303.5
42.5°	301.3
45°	298.3
47.5°	291.8
50°	280.8
52.5°	268.4
55°	255.3
57.5°	240.7
60°	223.9
62.5°	205.0
65°	185.3
67.5°	163.4
70°	141.5
72.5°	119.6
75°	99.2
77.5°	78.1
80°	59.1
82.5°	41.6
85°	24.1
87.5°	9.5
90°	0.0

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report





Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)