

Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P769240

Luminaire Tested: LD6D60D010-EU6DR6055659040-6LBSQW1B

Issue Date: 2/5/2024

**Test Information**

Test Method: LM-79-2019  
Report Number: P769240  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-57)  
Test Lab: COOPER LIGHTING SOLUTIONS  
Issue Date: 2/5/2024  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: PORTFOLIO  
Catalog Number: LD6D60D010-EU6DR6055659040-6LBSQW1B  
Description: 6 INCH SQAURE DEEP 45° CUTOFF SPECULAR BLACK TRIM, WITH 60° OPTIC  
Light Source: (1) HIGH LUMEN LED 90CRI / 4000K CCT  
Ballast/Driver: -

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 6060.6 lumens  
Efficiency: N/A  
Efficacy: 94.1 lumens/watt  
Spacing Criteria (0/90/45): 0.91 / 0.91 / 0.83  
Luminous Opening: Circular (Dia: 0.35' x H: 0')  
CIE Type: Direct


Input Watts (W): 64.4  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT



TEST NUMBER: P769240

CATALOG NUMBER: LD6D60D010-EU6DR6055659040-6LBSQW1B

### Luminous Intensity Polar Plot





TEST NUMBER: P769240

CATALOG NUMBER: LD6D60D010-EU6DR6055659040-6LBSQW1B

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	113	110	108	105	111	108	106	104	104	102	100	100	99	97	97	96	95	93																			
2	107	102	98	95	105	101	97	94	97	94	92	94	92	90	92	90	88	86																			
3	102	96	90	86	100	94	89	86	91	88	84	89	86	83	87	84	82	80																			
4	97	89	84	80	95	88	83	79	86	82	78	84	80	77	82	79	76	75																			
5	92	84	78	74	91	83	78	74	81	77	73	80	76	72	78	75	72	70																			
6	88	79	73	69	87	78	73	69	77	72	68	75	71	68	74	70	67	66																			
7	84	75	69	65	83	74	68	64	73	68	64	72	67	64	71	67	63	62																			
8	80	71	65	61	79	70	65	61	69	64	60	68	64	60	67	63	60	59																			
9	77	67	61	57	75	67	61	57	66	61	57	65	60	57	64	60	57	55																			
10	73	64	58	54	72	63	58	54	62	58	54	62	57	54	61	57	54	53																			

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	786437
5°	805772
10°	815511
15°	776874
20°	684963
25°	554027
30°	374743
35°	187790
40°	30466
45°	29822
50°	30409
55°	30878
60°	31729
65°	32446
70°	33224
75°	33603
80°	32404
85°	26953

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°  
 Vertical Angle: 75°  
 Luminance: 33603 cd/sqm



TEST NUMBER: P769240

CATALOG NUMBER: LD6D60D010-EU6DR6055659040-6LBSQW1B

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	702.2	11.6
10°-20°	1899.7	31.3
20°-30°	2044.0	33.7
30°-40°	888.5	14.7
40°-50°	149.2	2.5
50°-60°	145.1	2.4
60°-70°	124.1	2.0
70°-80°	83.0	1.4
80°-90°	24.8	0.4
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	4645.9	76.7
0°-40°	5534.3	91.3
0°-60°	5828.7	96.2
0°-90°	6060.6	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	6060.6	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	7198	
5°	7347	702
15°	6868	1900
25°	4596	2044
35°	1408	888
45°	193	149
55°	162	145
65°	126	124
75°	80	83
85°	22	25
90°	0	



TEST NUMBER: P769240

CATALOG NUMBER: LD6D60D010-EU6DR6055659040-6LBSQW1B

**CANDELA DISTRIBUTION (FULL):**

0°	
0°	7197.8
2.5°	7400.1
5°	7346.7
7.5°	7363.6
10°	7350.5
12.5°	7198.7
15°	6868.0
17.5°	6424.0
20°	5891.0
22.5°	5320.6
25°	4595.6
27.5°	3675.7
30°	2970.3
32.5°	2289.3
35°	1407.9
37.5°	602.3
40°	213.6
42.5°	196.7
45°	193.0
47.5°	186.4
50°	178.9
52.5°	170.5
55°	162.1
57.5°	153.6
60°	145.2
62.5°	135.8
65°	125.5
67.5°	115.2
70°	104.0
72.5°	91.8
75°	79.6
77.5°	65.6
80°	51.5
82.5°	36.5
85°	21.5
87.5°	7.5
90°	0.0

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report





Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)