

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P770033

Luminaire Tested: LD6D65D010-EU6DR6055659050-6LBSQW1B

Issue Date: 2/5/2024

Test Information

Test Method: LM-79-2019
Report Number: P770033
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-57)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/5/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD6D65D010-EU6DR6055659050-6LBSQW1B
Description: 6 INCH SQAURE DEEP 45° CUTOFF SPECULAR BLACK TRIM, WITH 60° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 5000K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 6750.8 lumens
Efficiency: N/A
Efficacy: 92.7 lumens/watt
Spacing Criteria (0/90/45): 0.91 / 0.91 / 0.83
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct


Input Watts (W): 72.8
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



TEST NUMBER: P770033

CATALOG NUMBER: LD6D65D010-EU6DR6055659050-6LBSQW1B

Luminous Intensity Polar Plot





TEST NUMBER: P770033

CATALOG NUMBER: LD6D65D010-EU6DR6055659050-6LBSQW1B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	113	110	108	105	111	108	106	104	104	102	100	100	99	97	97	96	95	93																			
2	107	102	98	95	105	101	97	94	97	94	92	94	92	90	92	90	88	86																			
3	102	96	90	86	100	94	89	86	91	88	84	89	86	83	87	84	82	80																			
4	97	89	84	80	95	88	83	79	86	82	78	84	80	77	82	79	76	75																			
5	92	84	78	74	91	83	78	74	81	77	73	80	76	72	78	75	72	70																			
6	88	79	73	69	87	78	73	69	77	72	68	75	71	68	74	70	67	66																			
7	84	75	69	65	83	74	68	64	73	68	64	72	67	64	71	67	63	62																			
8	80	71	65	61	79	70	65	61	69	64	60	68	64	60	67	63	60	59																			
9	77	67	61	57	75	67	61	57	66	61	57	65	60	57	64	60	57	55																			
10	73	64	58	54	72	63	58	54	62	58	54	62	57	54	61	57	54	53																			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	875998
5°	897540
10°	908373
15°	865353
20°	762971
25°	617114
30°	417424
35°	209171
40°	33932
45°	33206
50°	33877
55°	34384
60°	35335
65°	36143
70°	36993
75°	37445
80°	36117
85°	30087

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 75°
 Luminance: 37445 cd/sqm



TEST NUMBER: P770033

CATALOG NUMBER: LD6D65D010-EU6DR6055659050-6LBSQW1B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	782.1	11.6
10°-20°	2116.1	31.3
20°-30°	2276.7	33.7
30°-40°	989.6	14.7
40°-50°	166.2	2.5
50°-60°	161.6	2.4
60°-70°	138.2	2.0
70°-80°	92.5	1.4
80°-90°	27.7	0.4
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	5174.9	76.7
0°-40°	6164.6	91.3
0°-60°	6492.4	96.2
0°-90°	6750.8	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	6750.8	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	8018	
5°	8183	782
15°	7650	2116
25°	5119	2277
35°	1568	990
45°	215	166
55°	180	162
65°	140	138
75°	89	93
85°	24	28
90°	0	



TEST NUMBER: P770033

CATALOG NUMBER: LD6D65D010-EU6DR6055659050-6LBSQW1B

CANDELA DISTRIBUTION (FULL):

	0°
0°	8017.5
2.5°	8242.8
5°	8183.4
7.5°	8202.1
10°	8187.5
12.5°	8018.5
15°	7650.2
17.5°	7155.6
20°	6561.9
22.5°	5926.5
25°	5118.9
27.5°	4094.3
30°	3308.6
32.5°	2550.1
35°	1568.2
37.5°	670.9
40°	237.9
42.5°	219.1
45°	214.9
47.5°	207.6
50°	199.3
52.5°	189.9
55°	180.5
57.5°	171.1
60°	161.7
62.5°	151.3
65°	139.8
67.5°	128.3
70°	115.8
72.5°	102.3
75°	88.7
77.5°	73.0
80°	57.4
82.5°	40.7
85°	24.0
87.5°	8.3
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)