

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P771684

Luminaire Tested: LD6D75BD010-EU6DR7070959024-6LBSQW1B

Issue Date: 2/5/2024

Test Information

Test Method: LM-79-2019
Report Number: P771684
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-73)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/5/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD6D75BD010-EU6DR7070959024-6LBSQW1B
Description: 6 INCH SQAURE DEEP 45° CUTOFF SPECULAR BLACK TRIM, WITH 70° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 2400K CCT
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 4558.0 lumens
Efficiency: N/A
Efficacy: 63.0 lumens/watt
Spacing Criteria (0/90/45): 0.88 / 0.88 / 0.82
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 72.4
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



TEST NUMBER: P771684
CATALOG NUMBER: LD6D75BD010-EU6DR7070959024-6LBSQW1B

Luminous Intensity Polar Plot





TEST NUMBER: P771684

CATALOG NUMBER: LD6D75BD010-EU6DR7070959024-6LBSQW1B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	112	109	106	103	110	107	104	102	103	101	99	99	97	96	95	94	93	91																			
2	106	100	95	91	103	98	94	90	95	91	88	92	89	86	89	87	85	83																			
3	100	92	87	82	98	91	86	81	88	84	80	86	82	79	83	80	78	76																			
4	94	86	80	75	92	85	79	74	82	77	73	80	76	73	78	75	72	70																			
5	89	80	74	69	87	79	73	69	77	72	68	75	71	67	74	70	67	65																			
6	85	75	68	64	83	74	68	64	73	67	63	71	66	63	70	66	62	61																			
7	80	70	64	59	79	70	64	59	68	63	59	67	62	59	66	62	58	57																			
8	77	66	60	56	75	66	60	56	65	59	55	64	59	55	63	58	55	53																			
9	73	63	57	52	72	62	56	52	61	56	52	60	55	52	60	55	52	50																			
10	70	59	53	49	69	59	53	49	58	53	49	57	52	49	57	52	49	48																			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	559918
5°	543280
10°	528138
15°	521212
20°	486695
25°	365634
30°	258471
35°	91554
40°	48138
45°	51269
50°	53102
55°	54099
60°	54434
65°	53284
70°	50283
75°	46563
80°	41339
85°	33597

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 57.5°
 Luminance: 54458 cd/sqm



TEST NUMBER: P771684

CATALOG NUMBER: LD6D75BD010-EU6DR7070959024-6LBSQW1B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	467.2	10.3
10°-20°	1281.5	28.1
20°-30°	1411.4	31.0
30°-40°	539.3	11.8
40°-50°	254.6	5.6
50°-60°	253.2	5.6
60°-70°	202.7	4.4
70°-80°	116.5	2.6
80°-90°	31.6	0.7
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	3160.2	69.3
0°-40°	3699.5	81.2
0°-60°	4207.2	92.3
0°-90°	4558.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	4558.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	5125	
5°	4953	467
15°	4608	1282
25°	3033	1411
35°	686	539
45°	332	255
55°	284	253
65°	206	203
75°	110	116
85°	27	32
90°	0	



TEST NUMBER: P771684

CATALOG NUMBER: LD6D75BD010-EU6DR7070959024-6LBSQW1B

CANDELA DISTRIBUTION (FULL):

0°	
0°	5124.6
2.5°	5071.0
5°	4953.4
7.5°	4855.2
10°	4760.3
12.5°	4680.0
15°	4607.8
17.5°	4433.3
20°	4185.8
22.5°	3652.0
25°	3032.9
27.5°	2640.2
30°	2048.7
32.5°	1323.3
35°	686.4
37.5°	370.8
40°	337.5
42.5°	335.1
45°	331.8
47.5°	324.5
50°	312.4
52.5°	298.6
55°	284.0
57.5°	267.8
60°	249.1
62.5°	228.0
65°	206.1
67.5°	181.7
70°	157.4
72.5°	133.1
75°	110.3
77.5°	86.8
80°	65.7
82.5°	46.2
85°	26.8
87.5°	10.5
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)