

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P774037

Luminaire Tested: LD6D90BD010-EU6DR7070959027-6LBSQW1B

Issue Date: 2/5/2024

Test Information

Test Method: LM-79-2019
Report Number: P774037
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-73)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/5/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD6D90BD010-EU6DR7070959027-6LBSQW1B
Description: 6 INCH SQAURE DEEP 45° CUTOFF SPECULAR BLACK TRIM, WITH 70° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 2700K CCT
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 6606.4 lumens
Efficiency: N/A
Efficacy: 66.8 lumens/watt
Spacing Criteria (0/90/45): 0.88 / 0.88 / 0.82
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 98.9
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



TEST NUMBER: P774037
CATALOG NUMBER: LD6D90BD010-EU6DR7070959027-6LBSQW1B

Luminous Intensity Polar Plot





TEST NUMBER: P774037

CATALOG NUMBER: LD6D90BD010-EU6DR7070959027-6LBSQW1B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	112	109	106	103	110	107	104	102	103	101	99	99	97	96	95	94	93	91																			
2	106	100	95	91	103	98	94	90	95	91	88	92	89	86	89	87	85	83																			
3	100	92	87	82	98	91	86	81	88	84	80	86	82	79	83	80	78	76																			
4	94	86	80	75	92	85	79	74	82	77	73	80	76	73	78	75	72	70																			
5	89	80	74	69	87	79	73	69	77	72	68	75	71	67	74	70	67	65																			
6	85	75	68	64	83	74	68	64	73	67	63	71	66	63	70	66	62	61																			
7	80	70	64	59	79	70	64	59	68	63	59	67	62	59	66	62	58	57																			
8	77	66	60	56	75	66	60	56	65	59	55	64	59	55	63	58	55	53																			
9	73	63	57	52	72	62	56	52	61	56	52	60	55	52	60	55	52	50																			
10	70	59	53	49	69	59	53	49	58	53	49	57	52	49	57	52	49	48																			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	811534
5°	787423
10°	765474
15°	755428
20°	705416
25°	529940
30°	374630
35°	132703
40°	69774
45°	74323
50°	76967
55°	78406
60°	78886
65°	77224
70°	72868
75°	67502
80°	59963
85°	48641

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 57.5°
 Luminance: 78921 cd/sqm



TEST NUMBER: P774037

CATALOG NUMBER: LD6D90BD010-EU6DR7070959027-6LBSQW1B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	677.2	10.3
10°-20°	1857.5	28.1
20°-30°	2045.7	31.0
30°-40°	781.6	11.8
40°-50°	369.1	5.6
50°-60°	366.9	5.6
60°-70°	293.8	4.4
70°-80°	168.8	2.6
80°-90°	45.9	0.7
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	4580.3	69.3
0°-40°	5362.0	81.2
0°-60°	6098.0	92.3
0°-90°	6606.4	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	6606.4	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	7428	
5°	7179	677
15°	6678	1857
25°	4396	2046
35°	995	782
45°	481	369
55°	412	367
65°	299	294
75°	160	169
85°	39	46
90°	0	



TEST NUMBER: P774037

CATALOG NUMBER: LD6D90BD010-EU6DR7070959027-6LBSQW1B

CANDELA DISTRIBUTION (FULL):

	0°
0°	7427.5
2.5°	7349.9
5°	7179.4
7.5°	7037.1
10°	6899.5
12.5°	6783.1
15°	6678.4
17.5°	6425.6
20°	6066.9
22.5°	5293.1
25°	4395.8
27.5°	3826.7
30°	2969.4
32.5°	1918.0
35°	994.9
37.5°	537.4
40°	489.2
42.5°	485.7
45°	481.0
47.5°	470.4
50°	452.8
52.5°	432.8
55°	411.6
57.5°	388.1
60°	361.0
62.5°	330.5
65°	298.7
67.5°	263.4
70°	228.1
72.5°	192.9
75°	159.9
77.5°	125.8
80°	95.3
82.5°	67.0
85°	38.8
87.5°	15.3
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)