

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P773999

Luminaire Tested: LD6D90BD010-EU6DR6570959040-6LBSQW1MW

Issue Date: 2/5/2024

Test Information

Test Method: LM-79-2019
Report Number: P773999
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-59)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/5/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD6D90BD010-EU6DR6570959040-6LBSQW1MW
Description: 6 INCH SQAURE DEEP 45° CUTOFF MATTE WHITE TRIM, WITH 65° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 4000K CCT
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 9102.0 lumens
Efficiency: N/A
Efficacy: 92.0 lumens/watt
Spacing Criteria (0/90/45): 0.98 / 0.98 / 0.92
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 98.9
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



TEST NUMBER: P773999
CATALOG NUMBER: LD6D90BD010-EU6DR6570959040-6LBSQW1MW

Luminous Intensity Polar Plot





TEST NUMBER: P773999

CATALOG NUMBER: LD6D90BD010-EU6DR6570959040-6LBSQW1MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	113	111	108	106	111	108	106	104	104	103	101	101	99	98	97	96	95	93																			
2	108	103	99	95	106	101	97	94	98	95	92	95	92	90	92	90	88	87																			
3	102	96	91	87	100	94	90	86	92	88	85	89	86	83	87	84	82	80																			
4	97	89	84	79	95	88	83	79	86	82	78	84	80	77	82	79	76	75																			
5	92	83	78	73	90	83	77	73	81	76	72	79	75	72	77	74	71	69																			
6	87	78	72	68	86	77	72	68	76	71	67	74	70	67	73	69	66	65																			
7	83	73	67	63	81	73	67	63	71	66	62	70	66	62	69	65	62	60																			
8	79	69	63	59	77	68	63	59	67	62	58	66	62	58	65	61	58	57																			
9	75	65	59	55	74	65	59	55	64	58	55	63	58	55	62	58	54	53																			
10	71	61	56	52	70	61	55	52	60	55	51	59	55	51	59	54	51	50																			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	979151
5°	979963
10°	1014459
15°	1016135
20°	935531
25°	797116
30°	610215
35°	431106
40°	254480
45°	103311
50°	37446
55°	20859
60°	11975
65°	6593
70°	6900
75°	5361
80°	5600
85°	4764

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 103311 cd/sqm



TEST NUMBER: P773999

CATALOG NUMBER: LD6D90BD010-EU6DR6570959040-6LBSQW1MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	862.9	9.5
10°-20°	2489.1	27.3
20°-30°	2986.5	32.8
30°-40°	2007.0	22.1
40°-50°	600.8	6.6
50°-60°	106.0	1.2
60°-70°	30.2	0.3
70°-80°	14.8	0.2
80°-90°	4.7	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	6338.6	69.6
0°-40°	8345.6	91.7
0°-60°	9052.4	99.5
0°-90°	9102.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	9102.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	8962	
5°	8935	863
15°	8983	2489
25°	6612	2987
35°	3232	2007
45°	669	601
55°	110	106
65°	26	30
75°	13	15
85°	4	5
90°	0	



TEST NUMBER: P773999

CATALOG NUMBER: LD6D90BD010-EU6DR6570959040-6LBSQW1MW

CANDELA DISTRIBUTION (FULL):

0°	
0°	8961.6
2.5°	8999.8
5°	8934.9
7.5°	9069.8
10°	9143.7
12.5°	9125.9
15°	8983.2
17.5°	8634.3
20°	8046.0
22.5°	7353.2
25°	6612.0
27.5°	5775.3
30°	4836.7
32.5°	3986.0
35°	3232.1
37.5°	2487.1
40°	1784.2
42.5°	1165.2
45°	668.6
47.5°	354.0
50°	220.3
52.5°	152.8
55°	109.5
57.5°	79.0
60°	54.8
62.5°	35.7
65°	25.5
67.5°	22.9
70°	21.6
72.5°	16.6
75°	12.7
77.5°	11.5
80°	8.9
82.5°	6.4
85°	3.8
87.5°	2.5
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)