

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P774831

Luminaire Tested: LD6D95BD010-EU6DR7070959030-6LBSQW1MW

Issue Date: 2/5/2024

Test Information

Test Method: LM-79-2019
Report Number: P774831
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-73)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/5/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD6D95BD010-EU6DR7070959030-6LBSQW1MW
Description: 6 INCH SQAURE DEEP 45° CUTOFF MATTE WHITE TRIM, WITH 70° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 3000K CCT
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 9284.4 lumens
Efficiency: N/A
Efficacy: 93.6 lumens/watt
Spacing Criteria (0/90/45): 0.88 / 0.88 / 0.82
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 99.2
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



TEST NUMBER: P774831
CATALOG NUMBER: LD6D95BD010-EU6DR7070959030-6LBSQW1MW

Luminous Intensity Polar Plot





TEST NUMBER: P774831

CATALOG NUMBER: LD6D95BD010-EU6DR7070959030-6LBSQW1MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	112	109	106	103	110	107	104	102	103	101	99	99	97	96	95	94	93	91																			
2	106	100	95	91	103	98	94	90	95	91	88	92	89	86	89	87	85	83																			
3	100	92	87	82	98	91	86	81	88	84	80	86	82	79	83	80	78	76																			
4	94	86	80	75	92	85	79	74	82	77	73	80	76	73	78	75	72	70																			
5	89	80	74	69	87	79	73	69	77	72	68	75	71	67	74	70	67	65																			
6	85	75	68	64	83	74	68	64	73	67	63	71	66	63	70	66	62	61																			
7	80	70	64	59	79	70	64	59	68	63	59	67	62	59	66	62	58	57																			
8	77	66	60	56	75	66	60	56	65	59	55	64	59	55	63	58	55	53																			
9	73	63	57	52	72	62	56	52	61	56	52	60	55	52	60	55	52	50																			
10	70	59	53	49	69	59	53	49	58	53	49	57	52	49	57	52	49	48																			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	1140507
5°	1106619
10°	1075768
15°	1061653
20°	991366
25°	744770
30°	526480
35°	186496
40°	98058
45°	104439
50°	108158
55°	110180
60°	110878
65°	108532
70°	102418
75°	94900
80°	84251
85°	68323

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 57.5°
 Luminance: 110908 cd/sqm



TEST NUMBER: P774831

CATALOG NUMBER: LD6D95BD010-EU6DR7070959030-6LBSQW1MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	951.7	10.3
10°-20°	2610.4	28.1
20°-30°	2875.0	31.0
30°-40°	1098.5	11.8
40°-50°	518.7	5.6
50°-60°	515.6	5.6
60°-70°	412.8	4.4
70°-80°	237.3	2.6
80°-90°	64.5	0.7
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	6437.1	69.3
0°-40°	7535.5	81.2
0°-60°	8569.8	92.3
0°-90°	9284.4	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	9284.4	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	10438	
5°	10090	952
15°	9386	2610
25°	6178	2875
35°	1398	1098
45°	676	519
55°	578	516
65°	420	413
75°	225	237
85°	54	65
90°	0	



TEST NUMBER: P774831

CATALOG NUMBER: LD6D95BD010-EU6DR7070959030-6LBSQW1MW

CANDELA DISTRIBUTION (FULL):

0°	
0°	10438.4
2.5°	10329.3
5°	10089.7
7.5°	9889.7
10°	9696.3
12.5°	9532.7
15°	9385.6
17.5°	9030.3
20°	8526.2
22.5°	7438.8
25°	6177.8
27.5°	5377.8
30°	4173.0
32.5°	2695.5
35°	1398.2
37.5°	755.3
40°	687.5
42.5°	682.6
45°	675.9
47.5°	661.1
50°	636.3
52.5°	608.2
55°	578.4
57.5°	545.4
60°	507.4
62.5°	464.4
65°	419.8
67.5°	370.2
70°	320.6
72.5°	271.0
75°	224.8
77.5°	176.8
80°	133.9
82.5°	94.2
85°	54.5
87.5°	21.5
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)