

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P203221

Luminaire Tested: **LD6B10D010 EU6B10209730 6LBMH1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P203221
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD6B10D010 EU6B10209730 6LBMH1
Description: PORTFOLIO 6 INCH 50 DEGREE CUTOFF RECESSED DOWNLIGHT
MEDIUM DISTRIBUTION WITH SEMI-SPECULAR CLEAR TRIM
WATTAGE D010TR-10.05 W DE010-10.58 W D5LT-10.2 W DMX-10.6 W DL2-11.8 W
DL3-11.1 W DLE-11.39 W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 579.8 lumens
Efficiency: N/A
Efficacy: 58.6 lumens/watt
Spacing Criteria (0/90/45): 0.94 / 0.94 / 0.93
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 9.9
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P203221

CATALOG NUMBER: LD6B10D010 EU6B10209730 6LBMH1

Luminous Intensity Polar Plot





TEST NUMBER: P203221

CATALOG NUMBER: LD6B10D010 EU6B10209730 6LBMH1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			100
1	113	110	107	105	111	108	105	103	104	102	100	100	99	97	97	95	94	92			92
2	107	102	97	93	105	100	96	92	97	93	90	94	91	88	91	89	87	85			85
3	101	94	88	84	99	92	88	84	90	86	82	87	84	81	85	82	80	78			78
4	95	87	81	76	93	86	80	76	84	79	75	82	78	74	80	76	73	72			72
5	90	81	75	70	88	80	74	70	78	73	69	76	72	68	75	71	68	66			66
6	85	75	69	64	83	75	69	64	73	68	64	72	67	63	70	66	63	61			61
7	80	70	64	59	79	70	64	59	68	63	59	67	62	59	66	62	58	57			57
8	76	66	60	55	75	65	59	55	64	59	55	63	58	55	62	58	54	53			53
9	72	62	56	51	71	61	55	51	60	55	51	60	55	51	59	54	51	49			49
10	69	58	52	48	68	58	52	48	57	52	48	56	51	48	55	51	48	46			46

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P203221

CATALOG NUMBER: LD6B10D010 EU6B10209730 6LBMH1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	52.5	9.0
10°-20°	135.7	23.4
20°-30°	175.9	30.3
30°-40°	130.6	22.5
40°-50°	55.1	9.5
50°-60°	19.6	3.4
60°-70°	7.6	1.3
70°-80°	2.6	0.5
80°-90°	0.3	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	364.1	62.8
0°-40°	494.6	85.3
0°-60°	569.3	98.2
0°-90°	579.8	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	579.8	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	574	
5°	561	52
15°	484	136
25°	390	176
35°	207	131
45°	68	55
55°	21	20
65°	8	8
75°	2	3
85°	0	0
90°	0	



TEST NUMBER: P203221

CATALOG NUMBER: LD6B10D010 EU6B10209730 6LBMH1

CANDELA DISTRIBUTION (FULL):

	0°
0°	573.8
2.5°	572.2
5°	561.4
7.5°	545.7
10°	526.6
12.5°	505.9
15°	484.4
17.5°	460.4
20°	438.9
22.5°	416.5
25°	390.0
27.5°	353.6
30°	310.5
32.5°	260.0
35°	207.0
37.5°	162.3
40°	123.4
42.5°	91.9
45°	67.9
47.5°	49.7
50°	36.4
52.5°	27.3
55°	20.7
57.5°	15.7
60°	12.4
62.5°	9.1
65°	7.5
67.5°	5.8
70°	4.1
72.5°	3.3
75°	2.5
77.5°	1.7
80°	0.8
82.5°	0.8
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)