

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P205184

Luminaire Tested: **LD6B15D010 EU6B10209030 6LBWLI1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P205184
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD6B15D010 EU6B10209030 6LBWLI1
Description: PORTFOLIO 6 INCH 60 DEGREE CUTOFF RECESSED DOWNLIGHT
WIDE DISTRIBUTION WITH SPECULAR CLEAR TRIM
WATTAGE D010TR-14.39 W DE010-14.29 W D5LT-14.34 W DMX-14.46 W DL2-15.8 W
DL3-15.28 W DLE-15.432 W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1265.6 lumens
Efficiency: N/A
Efficacy: 88.5 lumens/watt
Spacing Criteria (0/90/45): 1.24 / 1.24 / 1.18
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 14.3
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P205184

CATALOG NUMBER: LD6B15D010 EU6B10209030 6LBWLI1

Luminous Intensity Polar Plot





TEST NUMBER: P205184

CATALOG NUMBER: LD6B15D010 EU6B10209030 6LBWLI1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			100																
1	113	110	107	104	110	107	105	103	103	101	99	100	98	97	96	95	94	92			92																
2	106	101	96	92	104	99	95	91	95	92	89	92	90	87	90	87	85	83			83																
3	100	92	87	82	97	91	86	81	88	84	80	86	82	79	83	80	77	76			76																
4	93	85	78	74	92	84	78	73	81	76	72	79	75	71	77	74	70	69			69																
5	88	78	71	66	86	77	71	66	75	70	65	73	69	65	72	68	64	63			63																
6	82	72	65	60	81	71	65	60	70	64	59	68	63	59	67	62	59	57			57																
7	77	67	60	55	76	66	59	55	65	59	54	63	58	54	62	57	54	52			52																
8	73	62	55	50	71	61	55	50	60	54	50	59	54	50	58	53	49	48			48																
9	69	57	51	46	67	57	50	46	56	50	46	55	50	46	54	49	46	44			44																
10	65	54	47	43	64	53	47	43	52	46	42	51	46	42	51	46	42	41			41																

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P205184

CATALOG NUMBER: LD6B15D010 EU6B10209030 6LBWLI1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	76.3	6.0
10°-20°	229.3	18.1
20°-30°	345.6	27.3
30°-40°	353.7	27.9
40°-50°	206.1	16.3
50°-60°	47.3	3.7
60°-70°	5.8	0.5
70°-80°	1.5	0.1
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	651.1	51.4
0°-40°	1004.9	79.4
0°-60°	1258.3	99.4
0°-90°	1265.6	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1265.6	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	791	
5°	795	76
15°	812	229
25°	758	346
35°	574	354
45°	266	206
55°	46	47
65°	4	6
75°	1	1
85°	0	0
90°	0	



TEST NUMBER: P205184

CATALOG NUMBER: LD6B15D010 EU6B10209030 6LBWLI1

CANDELA DISTRIBUTION (FULL):

	0°
0°	790.7
2.5°	789.2
5°	795.0
7.5°	800.7
10°	807.9
12.5°	809.3
15°	812.2
17.5°	809.3
20°	802.2
22.5°	779.2
25°	757.7
27.5°	723.2
30°	678.7
32.5°	632.8
35°	574.0
37.5°	508.0
40°	434.8
42.5°	353.0
45°	265.5
47.5°	185.1
50°	122.0
52.5°	77.5
55°	45.9
57.5°	24.4
60°	12.9
62.5°	7.2
65°	4.3
67.5°	4.3
70°	2.9
72.5°	1.4
75°	1.4
77.5°	1.4
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)