

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P205389

Luminaire Tested: **LD6B15D010 EU6B10209040 6LBSLI1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P205389
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD6B15D010 EU6B10209040 6LBSLI1
Description: PORTFOLIO 6 INCH SHALLOW RECESSED DOWNLIGHT
SHALLOW DISTRIBUTION WITH SPECULAR CLEAR TRIM
WATTAGE D010TR-14.39 W DE010-14.29 W D5LT-14.34 W DMX-14.46 W DL2-15.8 W
DL3-15.28 W DLE-15.432 W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1371.9 lumens
Efficiency: N/A
Efficacy: 95.9 lumens/watt
Spacing Criteria (0/90/45): 0.91 / 0.91 / 1.04
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 14.3
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P205389

CATALOG NUMBER: LD6B15D010 EU6B10209040 6LBSLI1

Luminous Intensity Polar Plot





TEST NUMBER: P205389

CATALOG NUMBER: LD6B15D010 EU6B10209040 6LBSLI1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20					
RC	80					70					50					30					10					0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0		
RCR																										
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100					100			
1	111	107	104	101	109	105	102	99	101	99	96	97	95	93	94	92	91	89					89			
2	103	96	91	86	100	94	89	85	91	87	83	88	84	81	85	82	79	77					77			
3	95	86	79	74	93	85	78	73	82	76	72	79	75	71	77	73	70	68					68			
4	88	78	70	64	86	77	69	64	74	68	63	72	67	62	70	65	62	60					60			
5	82	71	63	57	80	70	62	57	67	61	56	66	60	55	64	59	55	53					53			
6	76	64	56	51	74	63	56	51	62	55	50	60	54	50	59	53	49	47					47			
7	71	59	51	46	70	58	51	45	57	50	45	55	49	45	54	49	45	43					43			
8	67	54	47	41	65	54	46	41	52	46	41	51	45	41	50	45	41	39					39			
9	63	50	43	38	61	50	43	38	49	42	38	48	42	37	47	41	37	36					36			
10	59	47	40	35	58	46	39	35	45	39	35	45	39	34	44	38	34	33					33			

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P205389

CATALOG NUMBER: LD6B15D010 EU6B10209040 6LBSLI1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	79.8	5.8
10°-20°	203.1	14.8
20°-30°	259.0	18.9
30°-40°	268.6	19.6
40°-50°	247.5	18.0
50°-60°	186.2	13.6
60°-70°	100.5	7.3
70°-80°	27.0	2.0
80°-90°	0.4	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	541.8	39.5
0°-40°	810.4	59.1
0°-60°	1244.1	90.7
0°-90°	1371.9	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1371.9	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	866	
5°	853	80
15°	724	203
25°	563	259
35°	428	269
45°	322	247
55°	208	186
65°	101	100
75°	23	27
85°	0	0
90°	0	



TEST NUMBER: P205389

CATALOG NUMBER: LD6B15D010 EU6B10209040 6LBSLI1

CANDELA DISTRIBUTION (FULL):

	0°
0°	865.7
2.5°	862.8
5°	852.6
7.5°	833.7
10°	800.1
12.5°	766.6
15°	724.3
17.5°	685.0
20°	644.2
22.5°	601.9
25°	562.6
27.5°	524.7
30°	489.7
32.5°	457.6
35°	428.5
37.5°	400.8
40°	374.6
42.5°	346.9
45°	322.1
47.5°	294.4
50°	266.7
52.5°	237.6
55°	208.4
57.5°	179.3
60°	151.6
62.5°	125.3
65°	100.6
67.5°	77.2
70°	56.8
72.5°	39.4
75°	23.3
77.5°	10.2
80°	2.9
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)