

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P205395

Luminaire Tested: **LD6B20D010 EU6B10208035 6LBSLI1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P205395
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD6B20D010 EU6B10208035 6LBSLI1
Description: PORTFOLIO 6 INCH SHALLOW RECESSED DOWNLIGHT
SHALLOW DISTRIBUTION WITH SPECULAR CLEAR TRIM
WATTAGE D010TR-21.86 W DE010-20.46 W D5LT-21.24 W DMX-20.89 W DL2-22.5 W
DL3-21.8 6 W DLE-22.46 W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 2251.7 lumens
Efficiency: N/A
Efficacy: 108.3 lumens/watt
Spacing Criteria (0/90/45): 0.91 / 0.91 / 1.04
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 20.8
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P205395

CATALOG NUMBER: LD6B20D010 EU6B10208035 6LBSLI1

Luminous Intensity Polar Plot





TEST NUMBER: P205395

CATALOG NUMBER: LD6B20D010 EU6B10208035 6LBSLI1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	111	107	104	101	109	105	102	99	101	99	96	97	95	93	94	92	91	89			
2	103	96	91	86	100	94	89	85	91	87	83	88	84	81	85	82	79	77			
3	95	86	79	74	93	85	78	73	82	76	72	79	75	71	77	73	70	68			
4	88	78	70	64	86	77	69	64	74	68	63	72	67	62	70	65	62	60			
5	82	71	63	57	80	70	62	57	67	61	56	66	60	55	64	59	55	53			
6	76	64	56	51	74	63	56	51	62	55	50	60	54	50	59	53	49	47			
7	71	59	51	46	70	58	51	45	57	50	45	55	49	45	54	49	45	43			
8	67	54	47	41	65	54	46	41	52	46	41	51	45	41	50	45	41	39			
9	63	50	43	38	61	50	43	38	49	42	38	48	42	37	47	41	37	36			
10	59	47	40	35	58	46	39	35	45	39	35	45	39	34	44	38	34	33			

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P205395

CATALOG NUMBER: LD6B20D010 EU6B10208035 6LBSLI1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	130.9	5.8
10°-20°	333.3	14.8
20°-30°	425.1	18.9
30°-40°	440.8	19.6
40°-50°	406.2	18.0
50°-60°	305.5	13.6
60°-70°	164.9	7.3
70°-80°	44.2	2.0
80°-90°	0.7	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	889.3	39.5
0°-40°	1330.1	59.1
0°-60°	2041.8	90.7
0°-90°	2251.7	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2251.7	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1421	
5°	1399	131
15°	1189	333
25°	923	425
35°	703	441
45°	529	406
55°	342	306
65°	165	165
75°	38	44
85°	0	1
90°	0	



TEST NUMBER: P205395

CATALOG NUMBER: LD6B20D010 EU6B10208035 6LBSL11

CANDELA DISTRIBUTION (FULL):

0°	
0°	1420.9
2.5°	1416.1
5°	1399.4
7.5°	1368.3
10°	1313.3
12.5°	1258.2
15°	1188.9
17.5°	1124.3
20°	1057.3
22.5°	987.9
25°	923.3
27.5°	861.2
30°	803.7
32.5°	751.1
35°	703.3
37.5°	657.8
40°	614.8
42.5°	569.3
45°	528.7
47.5°	483.2
50°	437.8
52.5°	389.9
55°	342.1
57.5°	294.2
60°	248.8
62.5°	205.7
65°	165.1
67.5°	126.8
70°	93.3
72.5°	64.6
75°	38.3
77.5°	16.7
80°	4.8
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)