

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P204398

Luminaire Tested: **LD6B40D010 EU6B30508050 6LBSGPH1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P204398
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD6B40D010 EU6B30508050 6LBSGPH1
Description: PORTFOLIO 6 INCH SHALLOW RECESSED DOWNLIGHT
SHALLOW DISTRIBUTION WITH GRAPHITE HAZE TRIM
WATTAGE D010TR-43.02 W DE010-42.54 W D5LT-42.539 W DMX-41.87 W DL2-41.57
W DL3-44.71 W DLE-39.33 W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 4132.5 lumens
Efficiency: N/A
Efficacy: 98.9 lumens/watt
Spacing Criteria (0/90/45): 1.16 / 1.16 / 1.26
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 41.8
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P204398

CATALOG NUMBER: LD6B40D010 EU6B30508050 6LBSGPH1

Luminous Intensity Polar Plot





TEST NUMBER: P204398

CATALOG NUMBER: LD6B40D010 EU6B30508050 6LBSGPH1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			100
1	111	107	103	100	108	105	102	99	101	98	96	97	95	93	93	91	90	88			88
2	102	95	89	84	100	93	88	83	90	85	82	87	83	80	84	81	78	76			76
3	94	85	78	72	92	83	77	71	80	75	70	78	73	69	75	71	68	66			66
4	87	76	68	62	85	75	67	62	72	66	61	70	65	60	68	63	59	57			57
5	80	68	60	54	78	67	60	54	65	59	53	63	58	53	62	56	52	50			50
6	74	62	54	48	73	61	53	48	59	52	47	58	52	47	56	51	47	45			45
7	69	57	48	43	68	56	48	43	54	47	42	53	47	42	52	46	42	40			40
8	65	52	44	38	63	51	44	38	50	43	38	49	42	38	48	42	38	36			36
9	60	48	40	35	59	47	40	35	46	39	35	45	39	34	44	38	34	32			32
10	57	44	37	32	56	44	36	32	43	36	31	42	36	31	41	35	31	30			30

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P204398

CATALOG NUMBER: LD6B40D010 EU6B30508050 6LBSGPH1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	180.7	4.4
10°-20°	507.3	12.3
20°-30°	739.8	17.9
30°-40°	843.7	20.4
40°-50°	809.3	19.6
50°-60°	619.8	15.0
60°-70°	340.1	8.2
70°-80°	90.4	2.2
80°-90°	1.3	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1427.8	34.6
0°-40°	2271.5	55.0
0°-60°	3700.6	89.5
0°-90°	4132.5	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	4132.5	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1919	
5°	1904	181
15°	1800	507
25°	1607	740
35°	1349	844
45°	1051	809
55°	694	620
65°	342	340
75°	79	90
85°	0	1
90°	0	



TEST NUMBER: P204398

CATALOG NUMBER: LD6B40D010 EU6B30508050 6LBSGPH1

CANDELA DISTRIBUTION (FULL):

	0°
0°	1919.4
2.5°	1914.4
5°	1904.5
7.5°	1889.6
10°	1869.8
12.5°	1835.0
15°	1800.3
17.5°	1760.6
20°	1716.0
22.5°	1661.5
25°	1606.9
27.5°	1552.3
30°	1482.9
32.5°	1418.4
35°	1349.0
37.5°	1279.6
40°	1210.1
42.5°	1135.7
45°	1051.4
47.5°	967.1
50°	877.8
52.5°	783.6
55°	694.3
57.5°	605.1
60°	510.8
62.5°	421.6
65°	342.2
67.5°	262.9
70°	193.4
72.5°	128.9
75°	79.4
77.5°	34.7
80°	9.9
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)