

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P203162

Luminaire Tested: **LD6B40D010 EU6B30508050 6LBWMW1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P203162
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD6B40D010 EU6B30508050 6LBWMW1
Description: PORTFOLIO 6 INCH 60 DEGREE CUTOFF RECESSED DOWNLIGHT
WIDE DISTRIBUTION WITH MATTE WHITE TRIM
WATTAGE D010TR-43.02 W DE010-42.54 W D5LT-42.539 W DMX-41.87 W DL2-41.57
W DL3-44.71 W DLE-39.33 W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 4088.0 lumens
Efficiency: N/A
Efficacy: 97.8 lumens/watt
Spacing Criteria (0/90/45): 1.13 / 1.13 / 1.15
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 41.8
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P203162

CATALOG NUMBER: LD6B40D010 EU6B30508050 6LBWMW1

Luminous Intensity Polar Plot





TEST NUMBER: P203162

CATALOG NUMBER: LD6B40D010 EU6B30508050 6LBWMW1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	111	107	104	100	108	105	102	99	101	98	96	97	95	93	93	92	90	88			
2	103	96	90	86	100	94	89	85	91	86	83	88	84	81	85	82	79	77			
3	95	86	80	74	93	85	79	74	82	77	72	80	75	71	77	73	70	68			
4	89	78	71	65	86	77	70	65	75	69	64	72	67	63	70	66	62	60			
5	82	71	64	58	80	70	63	58	68	62	57	66	61	56	65	60	56	54			
6	77	65	57	52	75	64	57	52	63	56	51	61	55	51	60	54	50	49			
7	72	60	52	47	70	59	52	47	58	51	46	56	50	46	55	50	46	44			
8	67	55	48	42	66	55	47	42	53	47	42	52	46	42	51	46	42	40			
9	63	51	44	39	62	51	44	39	50	43	39	49	43	38	48	42	38	37			
10	60	48	40	36	58	47	40	36	46	40	36	45	40	35	45	39	35	34			

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P203162

CATALOG NUMBER: LD6B40D010 EU6B30508050 6LBWMW1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	216.2	5.3
10°-20°	606.3	14.8
20°-30°	873.6	21.4
30°-40°	907.0	22.2
40°-50°	670.5	16.4
50°-60°	400.5	9.8
60°-70°	243.4	6.0
70°-80°	133.4	3.3
80°-90°	37.1	0.9
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1696.1	41.5
0°-40°	2603.0	63.7
0°-60°	3674.1	89.9
0°-90°	4088.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	4088.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2296	
5°	2281	216
15°	2152	606
25°	1904	874
35°	1463	907
45°	863	671
55°	436	401
65°	243	243
75°	124	133
85°	30	37
90°	0	



TEST NUMBER: P203162

CATALOG NUMBER: LD6B40D010 EU6B30508050 6LBWMW1

CANDELA DISTRIBUTION (FULL):

	0°
0°	2295.6
2.5°	2295.6
5°	2280.8
7.5°	2260.9
10°	2231.2
12.5°	2196.5
15°	2151.9
17.5°	2102.3
20°	2052.7
22.5°	1983.3
25°	1903.9
27.5°	1819.7
30°	1710.6
32.5°	1601.5
35°	1462.7
37.5°	1318.9
40°	1160.2
42.5°	1006.5
45°	862.7
47.5°	733.8
50°	619.8
52.5°	520.6
55°	436.3
57.5°	371.9
60°	317.3
62.5°	277.7
65°	243.0
67.5°	213.2
70°	183.5
72.5°	153.7
75°	124.0
77.5°	99.2
80°	74.4
82.5°	54.5
85°	29.7
87.5°	14.9
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)