

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P204311

Luminaire Tested: **LD6B50D010TE EU6B30509030 6LBSWH1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P204311
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD6B50D010TE EU6B30509030 6LBSWH1
Description: PORTFOLIO 6 INCH SHALLOW RECESSED DOWNLIGHT
SHALLOW DISTRIBUTION WITH WHEAT TRIM
SINGLE DRIVER D010TE
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 4780.1 lumens
Efficiency: N/A
Efficacy: 81.3 lumens/watt
Spacing Criteria (0/90/45): 0.94 / 0.94 / 1.08
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 58.77
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P204311

CATALOG NUMBER: LD6B50D010TE EU6B30509030 6LBSWH1

Luminous Intensity Polar Plot





TEST NUMBER: P204311

CATALOG NUMBER: LD6B50D010TE EU6B30509030 6LBSWH1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				20	
RC	80				70				50				30				10				0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0	
RCR																						
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100				100
1	111	107	104	101	108	105	102	99	101	98	96	97	95	93	94	92	90	89				89
2	103	96	90	85	100	94	89	84	91	86	83	87	84	81	85	82	79	77				77
3	95	86	79	73	93	84	78	73	82	76	72	79	74	70	76	73	69	67				67
4	88	77	70	64	86	76	69	63	74	68	63	72	66	62	69	65	61	59				59
5	81	70	62	56	79	69	62	56	67	60	55	65	59	55	63	58	54	52				52
6	76	64	56	50	74	63	55	50	61	54	49	60	54	49	58	53	49	47				47
7	71	58	51	45	69	58	50	45	56	49	45	55	49	44	54	48	44	42				42
8	66	54	46	41	65	53	46	41	52	45	40	51	45	40	50	44	40	38				38
9	62	50	42	37	61	49	42	37	48	41	37	47	41	37	46	41	37	35				35
10	58	46	39	34	57	46	39	34	45	38	34	44	38	34	43	38	34	32				32

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P204311

CATALOG NUMBER: LD6B50D010TE EU6B30509030 6LBSWH1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	262.9	5.5
10°-20°	680.6	14.2
20°-30°	890.2	18.6
30°-40°	942.6	19.7
40°-50°	879.2	18.4
50°-60°	665.9	13.9
60°-70°	360.6	7.5
70°-80°	96.7	2.0
80°-90°	1.4	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1833.7	38.4
0°-40°	2776.3	58.1
0°-60°	4321.3	90.4
0°-90°	4780.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	4780.1	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2851	
5°	2809	263
15°	2432	681
25°	1935	890
35°	1506	943
45°	1146	879
55°	748	666
65°	361	361
75°	84	97
85°	0	1
90°	0	



TEST NUMBER: P204311

CATALOG NUMBER: LD6B50D010TE EU6B30509030 6LBSWH1

CANDELA DISTRIBUTION (FULL):

	0°
0°	2850.8
2.5°	2840.3
5°	2809.0
7.5°	2741.0
10°	2652.0
12.5°	2547.4
15°	2432.3
17.5°	2301.6
20°	2186.5
22.5°	2055.7
25°	1935.4
27.5°	1815.1
30°	1700.0
32.5°	1600.6
35°	1506.5
37.5°	1412.3
40°	1323.4
42.5°	1234.5
45°	1145.6
47.5°	1046.2
50°	946.8
52.5°	847.4
55°	748.0
57.5°	643.4
60°	544.0
62.5°	449.9
65°	360.9
67.5°	277.2
70°	204.0
72.5°	141.2
75°	83.7
77.5°	36.6
80°	10.5
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)