

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P203797

Luminaire Tested: **LD6B50D010TE EU6B30509035 6LBNWH1**

Issue Date: 3/3/2020

**Test Information**

Test Method: LM-41-14  
Report Number: P203797  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)  
Test Lab: INNOVATION CENTER-P3  
Issue Date: 3/3/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: io LED  
Catalog Number: LD6B50D010TE EU6B30509035 6LBNWH1  
Description: PORTFOLIO 6 INCH 50 DEGREE CUTOFF RECESSED DOWNLIGHT  
NARROW DISTRIBUTION WITH WHEAT TRIM  
SINGLE DRIVER D010TE  
Light Source: HIGH LUMEN LED  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 3119.2 lumens  
Efficiency: N/A  
Efficacy: 53.1 lumens/watt  
Spacing Criteria (0/90/45): 0.56 / 0.56 / 0.64  
Luminous Opening: Point Source (0' x 0' x 0')  
CIE Type: Direct


Input Watts (W): 58.77  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P203797

CATALOG NUMBER: LD6B50D010TE EU6B30509035 6LBNWH1

### Luminous Intensity Polar Plot





TEST NUMBER: P203797

CATALOG NUMBER: LD6B50D010TE EU6B30509035 6LBNWH1

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20			
RC	80				70				50				30				10		0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100		
1	114	111	109	107	112	109	107	105	105	104	102	101	100	99	98	97	96	94		
2	109	104	101	97	107	103	99	96	99	97	94	96	94	92	94	92	90	89		
3	104	98	93	90	102	97	92	89	94	91	88	92	89	86	89	87	85	83		
4	99	92	87	83	97	91	86	83	89	85	82	87	84	81	85	82	80	79		
5	95	87	82	78	93	86	81	77	84	80	77	83	79	76	81	78	75	74		
6	91	82	77	73	89	82	76	73	80	76	72	79	75	72	78	74	71	70		
7	87	78	73	69	85	77	72	69	76	72	68	75	71	68	74	70	67	66		
8	83	74	69	65	82	74	68	65	73	68	65	72	67	64	71	67	64	63		
9	79	71	65	62	78	70	65	61	69	65	61	68	64	61	68	64	61	60		
10	76	67	62	58	75	67	62	58	66	61	58	65	61	58	65	61	58	57		

**AVERAGE LUMINANCE (cd/sqm):**





TEST NUMBER: P203797

CATALOG NUMBER: LD6B50D010TE EU6B30509035 6LBNWH1

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	518.4	16.6
10°-20°	996.1	31.9
20°-30°	905.6	29.0
30°-40°	548.9	17.6
40°-50°	125.0	4.0
50°-60°	15.9	0.5
60°-70°	7.2	0.2
70°-80°	2.1	0.1
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2420.1	77.6
0°-40°	2969.0	95.2
0°-60°	3109.9	99.7
0°-90°	3119.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3119.2	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	6124	
5°	5774	518
15°	3587	996
25°	1964	906
35°	870	549
45°	138	125
55°	16	16
65°	5	7
75°	0	2
85°	0	0
90°	0	



TEST NUMBER: P203797

CATALOG NUMBER: LD6B50D010TE EU6B30509035 6LBNWH1

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	6124.0
2.5°	6049.7
5°	5773.7
7.5°	5328.0
10°	4760.1
12.5°	4171.1
15°	3587.3
17.5°	3056.7
20°	2610.9
22.5°	2250.1
25°	1963.5
27.5°	1708.8
30°	1459.3
32.5°	1167.5
35°	870.3
37.5°	610.3
40°	403.3
42.5°	249.4
45°	138.0
47.5°	63.7
50°	26.5
52.5°	21.2
55°	15.9
57.5°	15.9
60°	10.6
62.5°	10.6
65°	5.3
67.5°	5.3
70°	5.3
72.5°	5.3
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093







— 0°-180°







(END OF REPORT)