

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P204313

Luminaire Tested: **LD6B50D010TE EU6B30509040 6LBSWH1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P204313
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD6B50D010TE EU6B30509040 6LBSWH1
Description: PORTFOLIO 6 INCH SHALLOW RECESSED DOWNLIGHT
SHALLOW DISTRIBUTION WITH WHEAT TRIM
SINGLE DRIVER D010TE
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 4856.7 lumens
Efficiency: N/A
Efficacy: 82.6 lumens/watt
Spacing Criteria (0/90/45): 0.94 / 0.94 / 1.08
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 58.77
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P204313

CATALOG NUMBER: LD6B50D010TE EU6B30509040 6LBSWH1

Luminous Intensity Polar Plot





TEST NUMBER: P204313

CATALOG NUMBER: LD6B50D010TE EU6B30509040 6LBSWH1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	111	107	104	101	108	105	102	99	101	98	96	97	95	93	94	92	90	89			
2	103	96	90	85	100	94	89	84	91	86	83	87	84	81	85	82	79	77			
3	95	86	79	73	93	84	78	73	82	76	72	79	74	70	76	73	69	67			
4	88	77	70	64	86	76	69	63	74	68	63	72	66	62	69	65	61	59			
5	81	70	62	56	79	69	62	56	67	60	55	65	59	55	63	58	54	52			
6	76	64	56	50	74	63	55	50	61	54	49	60	54	49	58	53	49	47			
7	71	58	51	45	69	58	50	45	56	49	45	55	49	44	54	48	44	42			
8	66	54	46	41	65	53	46	41	52	45	40	51	45	40	50	44	40	38			
9	62	50	42	37	61	49	42	37	48	41	37	47	41	37	46	41	37	35			
10	58	46	39	34	57	46	39	34	45	38	34	44	38	34	43	38	34	32			

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P204313

CATALOG NUMBER: LD6B50D010TE EU6B30509040 6LBSWH1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	267.1	5.5
10°-20°	691.5	14.2
20°-30°	904.5	18.6
30°-40°	957.7	19.7
40°-50°	893.2	18.4
50°-60°	676.5	13.9
60°-70°	366.4	7.5
70°-80°	98.3	2.0
80°-90°	1.4	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1863.1	38.4
0°-40°	2820.8	58.1
0°-60°	4390.6	90.4
0°-90°	4856.7	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	4856.7	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2896	
5°	2854	267
15°	2471	691
25°	1966	904
35°	1531	958
45°	1164	893
55°	760	677
65°	367	366
75°	85	98
85°	0	1
90°	0	



TEST NUMBER: P204313

CATALOG NUMBER: LD6B50D010TE EU6B30509040 6LBSWH1

CANDELA DISTRIBUTION (FULL):

	0°
0°	2896.5
2.5°	2885.9
5°	2854.0
7.5°	2784.9
10°	2694.6
12.5°	2588.3
15°	2471.3
17.5°	2338.5
20°	2221.6
22.5°	2088.7
25°	1966.4
27.5°	1844.2
30°	1727.3
32.5°	1626.3
35°	1530.6
37.5°	1435.0
40°	1344.6
42.5°	1254.3
45°	1163.9
47.5°	1062.9
50°	962.0
52.5°	861.0
55°	760.0
57.5°	653.7
60°	552.7
62.5°	457.1
65°	366.7
67.5°	281.7
70°	207.3
72.5°	143.5
75°	85.0
77.5°	37.2
80°	10.6
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)