

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P203807

Luminaire Tested: **LD6B60D010TE EU6B60709024 6LBNWH1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P203807
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD6B60D010TE EU6B60709024 6LBNWH1
Description: PORTFOLIO 6 INCH 50 DEGREE CUTOFF RECESSED DOWNLIGHT
NARROW DISTRIBUTION WITH WHEAT TRIM
SINGLE DRIVER D010TE
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 2907.1 lumens
Efficiency: N/A
Efficacy: 46.5 lumens/watt
Spacing Criteria (0/90/45): 0.56 / 0.56 / 0.64
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 62.48
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P203807

CATALOG NUMBER: LD6B60D010TE EU6B60709024 6LBNWH1

Luminous Intensity Polar Plot





TEST NUMBER: P203807

CATALOG NUMBER: LD6B60D010TE EU6B60709024 6LBNWH1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20							
RC	80				70				50				30				10				0			
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0			
RCR																								
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100						
1	114	111	109	107	112	109	107	105	105	104	102	101	100	99	98	97	96	94						
2	109	104	101	97	107	103	99	96	99	97	94	96	94	92	94	92	90	89						
3	104	98	93	90	102	97	92	89	94	91	88	92	89	86	89	87	85	83						
4	99	92	87	83	97	91	86	83	89	85	82	87	84	81	85	82	80	79						
5	95	87	82	78	93	86	81	77	84	80	77	83	79	76	81	78	75	74						
6	91	82	77	73	89	82	76	73	80	76	72	79	75	72	78	74	71	70						
7	87	78	73	69	85	77	72	69	76	72	68	75	71	68	74	70	67	66						
8	83	74	69	65	82	74	68	65	73	68	65	72	67	64	71	67	64	63						
9	79	71	65	62	78	70	65	61	69	65	61	68	64	61	68	64	61	60						
10	76	67	62	58	75	67	62	58	66	61	58	65	61	58	65	61	58	57						

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P203807

CATALOG NUMBER: LD6B60D010TE EU6B60709024 6LBNWH1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	483.2	16.6
10°-20°	928.4	31.9
20°-30°	844.0	29.0
30°-40°	511.6	17.6
40°-50°	116.5	4.0
50°-60°	14.8	0.5
60°-70°	6.7	0.2
70°-80°	1.9	0.1
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2255.6	77.6
0°-40°	2767.2	95.2
0°-60°	2898.5	99.7
0°-90°	2907.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2907.1	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	5708	
5°	5381	483
15°	3344	928
25°	1830	844
35°	811	512
45°	129	116
55°	15	15
65°	5	7
75°	0	2
85°	0	0
90°	0	



TEST NUMBER: P203807

CATALOG NUMBER: LD6B60D010TE EU6B60709024 6LBNWH1

CANDELA DISTRIBUTION (FULL):

	0°
0°	5707.7
2.5°	5638.4
5°	5381.2
7.5°	4965.8
10°	4436.5
12.5°	3887.5
15°	3343.5
17.5°	2848.9
20°	2433.4
22.5°	2097.1
25°	1830.0
27.5°	1592.6
30°	1360.1
32.5°	1088.1
35°	811.1
37.5°	568.8
40°	375.9
42.5°	232.5
45°	128.6
47.5°	59.4
50°	24.7
52.5°	19.8
55°	14.8
57.5°	14.8
60°	9.9
62.5°	9.9
65°	4.9
67.5°	4.9
70°	4.9
72.5°	4.9
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)