

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P204323

Luminaire Tested: **LD6B60D010TE EU6B60709027 6LBSWH1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P204323
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD6B60D010TE EU6B60709027 6LBSWH1
Description: PORTFOLIO 6 INCH SHALLOW RECESSED DOWNLIGHT
SHALLOW DISTRIBUTION WITH WHEAT TRIM
SINGLE DRIVER D010TE
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 5136.6 lumens
Efficiency: N/A
Efficacy: 82.2 lumens/watt
Spacing Criteria (0/90/45): 0.94 / 0.94 / 1.08
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 62.48
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P204323

CATALOG NUMBER: LD6B60D010TE EU6B60709027 6LBSWH1

Luminous Intensity Polar Plot






TEST NUMBER: P204323

CATALOG NUMBER: LD6B60D010TE EU6B60709027 6LBSWH1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20
RC	80					70					50					30					10
RW	70	50	30	10		70	50	30	10		50	30	10		50	30	10		50	30	10
RCR																					
0	119	119	119	119		116	116	116	116		111	111	111		106	106	106		102	102	102
1	111	107	104	101		108	105	102	99		101	98	96		97	95	93		94	92	90
2	103	96	90	85		100	94	89	84		91	86	83		87	84	81		85	82	79
3	95	86	79	73		93	84	78	73		82	76	72		79	74	70		76	73	69
4	88	77	70	64		86	76	69	63		74	68	63		72	66	62		69	65	61
5	81	70	62	56		79	69	62	56		67	60	55		65	59	55		63	58	54
6	76	64	56	50		74	63	55	50		61	54	49		60	54	49		58	53	49
7	71	58	51	45		69	58	50	45		56	49	45		55	49	44		54	48	44
8	66	54	46	41		65	53	46	41		52	45	40		51	45	40		50	44	40
9	62	50	42	37		61	49	42	37		48	41	37		47	41	37		46	41	37
10	58	46	39	34		57	46	39	34		45	38	34		44	38	34		43	38	34

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P204323

CATALOG NUMBER: LD6B60D010TE EU6B60709027 6LBSWH1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	282.5	5.5
10°-20°	731.4	14.2
20°-30°	956.6	18.6
30°-40°	1012.9	19.7
40°-50°	944.7	18.4
50°-60°	715.5	13.9
60°-70°	387.6	7.5
70°-80°	103.9	2.0
80°-90°	1.5	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1970.5	38.4
0°-40°	2983.4	58.1
0°-60°	4643.6	90.4
0°-90°	5136.6	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	5136.6	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	3064	
5°	3018	283
15°	2614	731
25°	2080	957
35°	1619	1013
45°	1231	945
55°	804	716
65°	388	388
75°	90	104
85°	0	2
90°	0	



TEST NUMBER: P204323

CATALOG NUMBER: LD6B60D010TE EU6B60709027 6LBSWH1

CANDELA DISTRIBUTION (FULL):

0°	
0°	3063.5
2.5°	3052.2
5°	3018.5
7.5°	2945.4
10°	2849.9
12.5°	2737.5
15°	2613.8
17.5°	2473.3
20°	2349.6
22.5°	2209.1
25°	2079.8
27.5°	1950.5
30°	1826.8
32.5°	1720.0
35°	1618.9
37.5°	1517.7
40°	1422.1
42.5°	1326.6
45°	1231.0
47.5°	1124.2
50°	1017.4
52.5°	910.6
55°	803.8
57.5°	691.4
60°	584.6
62.5°	483.4
65°	387.9
67.5°	297.9
70°	219.2
72.5°	151.8
75°	89.9
77.5°	39.3
80°	11.2
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)