

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P203597

Luminaire Tested: **LD6B60D010TE EU6B60708030 6LBMMW1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P203597
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD6B60D010TE EU6B60708030 6LBMMW1
Description: PORTFOLIO 6 INCH 50 DEGREE CUTOFF RECESSED DOWNLIGHT
MEDIUM DISTRIBUTION WITH MATTE WHITE TRIM
SINGLE DRIVER D010TE
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 4789.4 lumens
Efficiency: N/A
Efficacy: 76.7 lumens/watt
Spacing Criteria (0/90/45): 1 / 1 / 0.97
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 62.48
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P203597

CATALOG NUMBER: LD6B60D010TE EU6B60708030 6LBMMW1

Luminous Intensity Polar Plot






TEST NUMBER: P203597

CATALOG NUMBER: LD6B60D010TE EU6B60708030 6LBMMW1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20							
RC	80				70				50				30				10				0			
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0			
RCR																								
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100						
1	111	108	104	101	109	105	103	100	101	99	97	98	96	94	94	92	91	89						
2	104	97	92	88	101	96	91	87	92	88	85	89	86	83	86	83	81	79						
3	97	88	82	77	95	87	81	76	84	79	75	82	77	74	79	76	73	71						
4	90	81	74	68	88	80	73	68	77	72	67	75	70	66	73	69	65	64						
5	85	74	67	61	83	73	66	61	71	65	61	69	64	60	68	63	59	58						
6	79	68	61	56	78	68	61	56	66	60	55	64	59	55	63	58	54	53						
7	75	63	56	51	73	63	56	51	61	55	50	60	54	50	59	54	50	48						
8	70	59	52	47	69	58	51	47	57	51	46	56	50	46	55	50	46	44						
9	66	55	48	43	65	54	48	43	53	47	43	52	47	43	51	46	43	41						
10	63	51	45	40	62	51	44	40	50	44	40	49	44	40	48	43	40	38						

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P203597

CATALOG NUMBER: LD6B60D010TE EU6B60708030 6LBMMW1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	330.1	6.9
10°-20°	884.3	18.5
20°-30°	1187.3	24.8
30°-40°	973.9	20.3
40°-50°	584.9	12.2
50°-60°	388.7	8.1
60°-70°	260.5	5.4
70°-80°	140.2	2.9
80°-90°	39.5	0.8
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2401.7	50.1
0°-40°	3375.6	70.5
0°-60°	4349.2	90.8
0°-90°	4789.4	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	4789.4	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	3574	
5°	3514	330
15°	3151	884
25°	2616	1187
35°	1546	974
45°	740	585
55°	429	389
65°	264	261
75°	132	140
85°	33	40
90°	0	



TEST NUMBER: P203597

CATALOG NUMBER: LD6B60D010TE EU6B60708030 6LBMMW1

CANDELA DISTRIBUTION (FULL):

	0°
0°	3573.7
2.5°	3547.3
5°	3514.3
7.5°	3441.6
10°	3355.7
12.5°	3250.0
15°	3150.9
17.5°	3032.0
20°	2913.1
22.5°	2781.0
25°	2615.9
27.5°	2417.7
30°	2153.5
32.5°	1856.2
35°	1545.7
37.5°	1281.5
40°	1056.9
42.5°	878.6
45°	739.8
47.5°	627.5
50°	548.3
52.5°	482.2
55°	429.4
57.5°	383.1
60°	343.5
62.5°	297.3
65°	264.2
67.5°	224.6
70°	191.6
72.5°	158.5
75°	132.1
77.5°	105.7
80°	79.3
82.5°	59.5
85°	33.0
87.5°	13.2
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)