

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P204628

Luminaire Tested: **LD6B60D010TE EU6B60708030 6LBSMW1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P204628
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD6B60D010TE EU6B60708030 6LB5MW1
Description: PORTFOLIO 6 INCH SHALLOW RECESSED DOWNLIGHT
SHALLOW DISTRIBUTION WITH MATTE WHITE TRIM
SINGLE DRIVER D010TE
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 6486.1 lumens
Efficiency: N/A
Efficacy: 103.8 lumens/watt
Spacing Criteria (0/90/45): 1.24 / 1.24 / 1.34
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 62.48
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P204628

CATALOG NUMBER: LD6B60D010TE EU6B60708030 6LBSMW1

Luminous Intensity Polar Plot






TEST NUMBER: P204628

CATALOG NUMBER: LD6B60D010TE EU6B60708030 6LBSMW1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20					20					20					20
RC	80				70					50					30					0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100		
1	110	106	102	99	107	104	100	97	99	97	94	96	93	91	92	90	88	86		
2	101	93	87	82	98	92	86	81	88	83	79	85	81	77	82	79	76	74		
3	93	83	75	69	90	81	74	69	78	72	67	76	70	66	73	69	65	63		
4	85	74	66	59	83	72	65	59	70	63	58	68	62	57	66	61	56	54		
5	78	66	58	51	76	65	57	51	63	56	51	61	55	50	59	54	49	47		
6	73	60	51	45	71	59	51	45	57	50	44	55	49	44	54	48	44	42		
7	67	54	46	40	66	54	46	40	52	45	40	51	44	39	49	43	39	37		
8	63	50	41	36	61	49	41	36	48	41	35	46	40	35	45	39	35	33		
9	59	46	38	32	57	45	37	32	44	37	32	43	36	32	42	36	32	30		
10	55	42	34	29	54	42	34	29	41	34	29	40	33	29	39	33	29	27		

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P204628

CATALOG NUMBER: LD6B60D010TE EU6B60708030 6LBSMW1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	247.6	3.8
10°-20°	705.8	10.9
20°-30°	1063.0	16.4
30°-40°	1264.9	19.5
40°-50°	1262.5	19.5
50°-60°	1026.8	15.8
60°-70°	631.7	9.7
70°-80°	244.7	3.8
80°-90°	39.2	0.6
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2016.4	31.1
0°-40°	3281.3	50.6
0°-60°	5570.6	85.9
0°-90°	6486.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	6486.1	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2613	
5°	2606	248
15°	2506	706
25°	2314	1063
35°	2025	1265
45°	1641	1263
55°	1149	1027
65°	634	632
75°	223	245
85°	31	39
90°	0	



TEST NUMBER: P204628

CATALOG NUMBER: LD6B60D010TE EU6B60708030 6LBSMW1

CANDELA DISTRIBUTION (FULL):

	0°
0°	2613.3
2.5°	2617.1
5°	2605.6
7.5°	2590.2
10°	2571.0
12.5°	2536.4
15°	2505.7
17.5°	2459.6
20°	2409.6
22.5°	2363.5
25°	2313.5
27.5°	2244.4
30°	2175.2
32.5°	2109.9
35°	2025.3
37.5°	1933.1
40°	1848.5
42.5°	1744.8
45°	1641.0
47.5°	1529.5
50°	1410.4
52.5°	1287.4
55°	1149.1
57.5°	1014.6
60°	883.9
62.5°	757.1
65°	634.1
67.5°	518.8
70°	411.2
72.5°	311.3
75°	222.9
77.5°	146.0
80°	88.4
82.5°	53.8
85°	30.7
87.5°	15.4
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)