

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P205046

Luminaire Tested: **LD6B60D010TE EU6B60709030 6LBCSMMS1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P205046
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD6B60D010TE EU6B60709030 6LBCSMMS1
Description: PORTFOLIO 6 INCH SHALLOW RECESSED DOWNLIGHT
SHALLOW DISTRIBUTION WITH CAST MATTE METALLIC SILVER TRIM
SINGLE DRIVER D010TE
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 5245.6 lumens
Efficiency: N/A
Efficacy: 84.0 lumens/watt
Spacing Criteria (0/90/45): 1.16 / 1.16 / 1.27
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 62.48
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P205046

CATALOG NUMBER: LD6B60D010TE EU6B60709030 6LBCSMMS1

Luminous Intensity Polar Plot






TEST NUMBER: P205046

CATALOG NUMBER: LD6B60D010TE EU6B60709030 6LBCSMMS1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20					20					20					20
RC	80				70					50					30					0
RW	70	50	30	10	70	50	30	10		50	30	10		50	30	10		50	30	10
RCR																				
0	119	119	119	119	116	116	116	116		111	111	111		106	106	106		102	102	102
1	111	107	103	100	108	105	101	98		100	98	95		97	94	92		93	91	90
2	102	95	89	84	99	93	88	83		90	85	81		86	83	79		83	80	78
3	94	85	77	72	92	83	76	71		80	74	70		77	73	69		75	71	67
4	87	76	68	62	84	74	67	61		72	66	61		70	64	60		68	63	59
5	80	68	60	54	78	67	59	54		65	58	53		63	57	53		61	56	52
6	74	62	54	48	72	61	53	47		59	52	47		58	51	47		56	51	46
7	69	56	48	42	67	56	48	42		54	47	42		53	46	42		51	46	41
8	64	52	44	38	63	51	43	38		50	43	38		48	42	38		47	42	37
9	60	48	40	35	59	47	40	34		46	39	34		45	39	34		44	38	34
10	57	44	36	31	55	43	36	31		43	36	31		42	35	31		41	35	31

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P205046

CATALOG NUMBER: LD6B60D010TE EU6B60709030 6LBCSMMS1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	227.0	4.3
10°-20°	637.0	12.1
20°-30°	930.4	17.7
30°-40°	1064.1	20.3
40°-50°	1022.7	19.5
50°-60°	789.7	15.1
60°-70°	440.8	8.4
70°-80°	128.3	2.4
80°-90°	5.5	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1794.4	34.2
0°-40°	2858.5	54.5
0°-60°	4671.0	89.0
0°-90°	5245.6	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	5245.6	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2409	
5°	2388	227
15°	2260	637
25°	2022	930
35°	1703	1064
45°	1333	1023
55°	886	790
65°	441	441
75°	112	128
85°	3	6
90°	0	



TEST NUMBER: P205046

CATALOG NUMBER: LD6B60D010TE EU6B60709030 6LBCSMMS1

CANDELA DISTRIBUTION (FULL):

0°	
0°	2408.9
2.5°	2408.9
5°	2388.5
7.5°	2378.4
10°	2344.4
12.5°	2303.7
15°	2259.6
17.5°	2215.5
20°	2151.0
22.5°	2100.1
25°	2022.1
27.5°	1944.1
30°	1866.0
32.5°	1788.0
35°	1703.2
37.5°	1618.4
40°	1520.0
42.5°	1431.8
45°	1333.4
47.5°	1221.4
50°	1116.2
52.5°	1000.9
55°	885.5
57.5°	766.8
60°	654.8
62.5°	542.8
65°	441.1
67.5°	346.1
70°	257.9
72.5°	179.8
75°	112.0
77.5°	57.7
80°	20.4
82.5°	6.8
85°	3.4
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)