

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P205147

Luminaire Tested: **LD6B60D010TE EU6B60709030 6LBMLI1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P205147
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD6B60D010TE EU6B60709030 6LBMLI1
Description: PORTFOLIO 6 INCH 50 DEGREE CUTOFF RECESSED DOWNLIGHT
MEDIUM DISTRIBUTION WITH SPECULAR CLEAR TRIM
SINGLE DRIVER D010TE
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 4563.6 lumens
Efficiency: N/A
Efficacy: 73.0 lumens/watt
Spacing Criteria (0/90/45): 0.85 / 0.85 / 0.85
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 62.48
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P205147

CATALOG NUMBER: LD6B60D010TE EU6B60709030 6LBMLI1

Luminous Intensity Polar Plot





TEST NUMBER: P205147

CATALOG NUMBER: LD6B60D010TE EU6B60709030 6LBMLI1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20
RC	80					70					50					30					10
RW	70	50	30	10		70	50	30	10		50	30	10			50	30	10			0
RCR																					
0	119	119	119	119		116	116	116	116		111	111	111			106	106	106			100
1	114	111	109	106		111	109	107	105		105	103	101			101	100	98			94
2	108	103	100	96		106	102	98	95		99	96	93			96	93	91			88
3	103	97	92	88		101	95	91	87		93	89	86			90	87	85			82
4	98	91	85	81		96	89	84	81		87	83	80			85	82	79			76
5	93	85	79	75		91	84	79	75		82	78	74			81	77	73			71
6	89	80	74	70		87	79	74	70		78	73	69			76	72	69			67
7	84	75	69	65		83	75	69	65		73	68	65			72	68	64			63
8	80	71	65	61		79	70	65	61		69	64	61			68	64	60			59
9	77	67	61	57		75	67	61	57		66	61	57			65	60	57			55
10	73	64	58	54		72	63	58	54		62	57	54			62	57	54			52

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P205147

CATALOG NUMBER: LD6B60D010TE EU6B60709030 6LBMLI1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	526.1	11.5
10°-20°	1309.9	28.7
20°-30°	1522.7	33.4
30°-40°	932.4	20.4
40°-50°	231.5	5.1
50°-60°	27.1	0.6
60°-70°	10.1	0.2
70°-80°	3.8	0.1
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	3358.6	73.6
0°-40°	4291.1	94.0
0°-60°	4549.7	99.7
0°-90°	4563.6	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	4563.6	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	5711	
5°	5635	526
15°	4701	1310
25°	3370	1523
35°	1460	932
45°	257	232
55°	23	27
65°	12	10
75°	6	4
85°	0	0
90°	0	



TEST NUMBER: P205147

CATALOG NUMBER: LD6B60D010TE EU6B60709030 6LBMLI1

CANDELA DISTRIBUTION (FULL):

0°	
0°	5711.2
2.5°	5705.3
5°	5635.3
7.5°	5483.4
10°	5279.0
12.5°	5010.4
15°	4700.9
17.5°	4368.1
20°	4041.0
22.5°	3714.0
25°	3369.5
27.5°	2972.4
30°	2516.9
32.5°	1985.5
35°	1459.9
37.5°	1027.8
40°	700.8
42.5°	438.0
45°	256.9
47.5°	146.0
50°	75.9
52.5°	35.0
55°	23.4
57.5°	17.5
60°	17.5
62.5°	11.7
65°	11.7
67.5°	5.8
70°	5.8
72.5°	5.8
75°	5.8
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)