

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P205560

Luminaire Tested: **LD6B60D010TE EU6B60709730 6LBMGPH1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P205560
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD6B60D010TE EU6B60709730 6LBMGPH1
Description: PORTFOLIO 6 INCH 50 DEGREE CUTOFF RECESSED DOWNLIGHT
MEDIUM DISTRIBUTION WITH GRAPHITE HAZE TRIM
SINGLE DRIVER D010TE
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 2487.4 lumens
Efficiency: N/A
Efficacy: 39.8 lumens/watt
Spacing Criteria (0/90/45): 0.94 / 0.94 / 0.91
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 62.48
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P205560

CATALOG NUMBER: LD6B60D010TE EU6B60709730 6LBMGPH1

Luminous Intensity Polar Plot





TEST NUMBER: P205560

CATALOG NUMBER: LD6B60D010TE EU6B60709730 6LBMGPH1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	108	105	111	108	106	104	104	102	101		100	99	98		97
2	107	102	98	94	105	100	97	93	97	94	91		94	92	89		91
3	102	95	90	85	100	93	89	85	91	87	83		88	85	82		86
4	96	88	82	78	94	87	82	77	85	80	77		83	79	76		81
5	91	82	76	72	89	81	76	71	79	74	71		78	73	70		76
6	86	77	71	66	85	76	70	66	74	69	65		73	68	65		72
7	82	72	66	61	80	71	65	61	70	65	61		69	64	60		68
8	77	68	61	57	76	67	61	57	66	60	57		65	60	56		64
9	74	64	57	53	72	63	57	53	62	57	53		61	56	53		60
10	70	60	54	50	69	59	54	50	59	53	50		58	53	49		57

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P205560

CATALOG NUMBER: LD6B60D010TE EU6B60709730 6LBMGPH1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	238.1	9.6
10°-20°	617.9	24.8
20°-30°	787.3	31.7
30°-40°	556.4	22.4
40°-50°	203.1	8.2
50°-60°	56.3	2.3
60°-70°	20.4	0.8
70°-80°	7.2	0.3
80°-90°	0.7	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1643.3	66.1
0°-40°	2199.6	88.4
0°-60°	2459.0	98.9
0°-90°	2487.4	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2487.4	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2592	
5°	2547	238
15°	2200	618
25°	1748	787
35°	884	556
45°	246	203
55°	60	56
65°	20	20
75°	5	7
85°	0	1
90°	0	



TEST NUMBER: P205560

CATALOG NUMBER: LD6B60D010TE EU6B60709730 6LBMGPH1

CANDELA DISTRIBUTION (FULL):

	0°
0°	2592.0
2.5°	2582.0
5°	2546.8
7.5°	2476.5
10°	2401.1
12.5°	2300.7
15°	2200.2
17.5°	2099.7
20°	1999.3
22.5°	1878.7
25°	1748.1
27.5°	1567.3
30°	1366.3
32.5°	1125.2
35°	884.1
37.5°	673.1
40°	492.3
42.5°	356.7
45°	246.1
47.5°	165.8
50°	110.5
52.5°	75.3
55°	60.3
57.5°	45.2
60°	35.2
62.5°	25.1
65°	20.1
67.5°	15.1
70°	10.0
72.5°	10.0
75°	5.0
77.5°	5.0
80°	5.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)