

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P203907

Luminaire Tested: **LD6B60D010TE EU6B60708035 6LBNGPH1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P203907
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD6B60D010TE EU6B60708035 6LBNGPH1
Description: PORTFOLIO 6 INCH 50 DEGREE CUTOFF RECESSED DOWNLIGHT
NARROW DISTRIBUTION WITH GRAPHITE HAZE TRIM
SINGLE DRIVER D010TE
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 3080.7 lumens
Efficiency: N/A
Efficacy: 49.3 lumens/watt
Spacing Criteria (0/90/45): 0.84 / 0.84 / 0.88
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 62.48
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P203907

CATALOG NUMBER: LD6B60D010TE EU6B60708035 6LBNGPH1

Luminous Intensity Polar Plot





TEST NUMBER: P203907

CATALOG NUMBER: LD6B60D010TE EU6B60708035 6LBNGPH1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	111	108	106	111	109	106	104	105	103	101		101	100	98		97
2	108	103	99	96	106	101	98	95	98	95	93		95	93	91		92
3	103	96	91	87	101	95	90	87	92	88	85		90	87	84		88
4	97	90	84	80	96	89	84	80	87	82	79		85	81	78		83
5	93	84	78	74	91	83	78	74	82	77	73		80	76	73		78
6	88	79	73	69	86	78	73	69	77	72	68		75	71	68		74
7	84	74	68	64	82	74	68	64	72	67	64		71	67	63		70
8	79	70	64	60	78	69	64	60	68	63	60		67	63	59		66
9	76	66	60	56	75	66	60	56	65	60	56		64	59	56		63
10	72	63	57	53	71	62	57	53	61	56	53		61	56	53		60

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P203907

CATALOG NUMBER: LD6B60D010TE EU6B60708035 6LBNGPH1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	339.0	11.0
10°-20°	836.0	27.1
20°-30°	1012.9	32.9
30°-40°	690.3	22.4
40°-50°	164.4	5.3
50°-60°	25.7	0.8
60°-70°	9.5	0.3
70°-80°	2.7	0.1
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2188.0	71.0
0°-40°	2878.3	93.4
0°-60°	3068.4	99.6
0°-90°	3080.7	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3080.7	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	3745	
5°	3639	339
15°	2993	836
25°	2213	1013
35°	1103	690
45°	176	164
55°	28	26
65°	7	10
75°	0	3
85°	0	0
90°	0	



TEST NUMBER: P203907

CATALOG NUMBER: LD6B60D010TE EU6B60708035 6LBNGPH1

CANDELA DISTRIBUTION (FULL):

0°	
0°	3744.6
2.5°	3723.5
5°	3639.2
7.5°	3526.8
10°	3365.2
12.5°	3182.6
15°	2992.9
17.5°	2796.2
20°	2599.4
22.5°	2402.7
25°	2213.0
27.5°	2037.4
30°	1784.5
32.5°	1454.3
35°	1103.0
37.5°	786.9
40°	519.9
42.5°	323.2
45°	175.6
47.5°	91.3
50°	49.2
52.5°	35.1
55°	28.1
57.5°	21.1
60°	14.1
62.5°	14.1
65°	7.0
67.5°	7.0
70°	7.0
72.5°	7.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)