

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P202774

Luminaire Tested: **LD6B60D010TE EU6B60708035 6LBWH1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P202774
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD6B60D010TE EU6B60708035 6LBWH1
Description: PORTFOLIO 6 INCH 60 DEGREE CUTOFF RECESSED DOWNLIGHT
WIDE DISTRIBUTION WITH SEMI-SPECULAR CLEAR TRIM
SINGLE DRIVER D010TE
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 5417.5 lumens
Efficiency: N/A
Efficacy: 86.7 lumens/watt
Spacing Criteria (0/90/45): 1.16 / 1.16 / 1.16
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 62.48
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P202774

CATALOG NUMBER: LD6B60D010TE EU6B60708035 6LBWH1

Luminous Intensity Polar Plot






TEST NUMBER: P202774

CATALOG NUMBER: LD6B60D010TE EU6B60708035 6LBWH1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	112	109	106	103	110	107	104	101	103	100	98		99	97	95		95
2	105	99	94	90	103	97	93	89	94	90	87		91	88	85		88
3	98	90	84	79	96	89	83	78	86	81	77		83	79	76		81
4	92	82	75	70	90	81	75	70	79	73	69		77	72	68		75
5	86	75	68	63	84	74	68	63	72	66	62		71	65	61		69
6	80	69	62	57	78	68	61	56	67	61	56		65	60	56		64
7	75	64	56	51	73	63	56	51	62	55	51		60	55	51		59
8	70	59	52	47	69	58	51	47	57	51	46		56	50	46		55
9	66	55	48	43	65	54	47	43	53	47	43		52	47	42		51
10	62	51	44	40	61	50	44	39	50	43	39		49	43	39		48

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P202774

CATALOG NUMBER: LD6B60D010TE EU6B60708035 6LBWH1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	315.6	5.8
10°-20°	895.5	16.5
20°-30°	1313.0	24.2
30°-40°	1366.5	25.2
40°-50°	945.5	17.5
50°-60°	411.6	7.6
60°-70°	126.2	2.3
70°-80°	37.9	0.7
80°-90°	5.7	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2524.1	46.6
0°-40°	3890.6	71.8
0°-60°	5247.7	96.9
0°-90°	5417.5	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	5417.5	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	3342	
5°	3327	316
15°	3180	896
25°	2871	1313
35°	2211	1367
45°	1222	945
55°	442	412
65°	119	126
75°	35	38
85°	7	6
90°	0	



TEST NUMBER: P202774

CATALOG NUMBER: LD6B60D010TE EU6B60708035 6LBWH1

CANDELA DISTRIBUTION (FULL):

0°	
0°	3341.5
2.5°	3348.5
5°	3327.4
7.5°	3299.3
10°	3264.2
12.5°	3229.1
15°	3180.0
17.5°	3116.8
20°	3046.6
22.5°	2969.4
25°	2871.1
27.5°	2744.8
30°	2583.3
32.5°	2414.8
35°	2211.3
37.5°	1986.6
40°	1726.9
42.5°	1467.1
45°	1221.5
47.5°	989.8
50°	786.2
52.5°	596.7
55°	442.3
57.5°	315.9
60°	217.6
62.5°	161.5
65°	119.3
67.5°	91.3
70°	63.2
72.5°	49.1
75°	35.1
77.5°	21.1
80°	14.0
82.5°	7.0
85°	7.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)