

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P205448

Luminaire Tested: **LD6B60D010TE EU6B60708040 6LBSLI1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P205448
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD6B60D010TE EU6B60708040 6LBSLI1
Description: PORTFOLIO 6 INCH SHALLOW RECESSED DOWNLIGHT
SHALLOW DISTRIBUTION WITH SPECULAR CLEAR TRIM
SINGLE DRIVER D010TE
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 6669.2 lumens
Efficiency: N/A
Efficacy: 106.7 lumens/watt
Spacing Criteria (0/90/45): 0.91 / 0.91 / 1.04
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 62.48
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P205448

CATALOG NUMBER: LD6B60D010TE EU6B60708040 6LBSLI1

Luminous Intensity Polar Plot





TEST NUMBER: P205448

CATALOG NUMBER: LD6B60D010TE EU6B60708040 6LBSLI1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20					20					20					20
RC	80				70					50					30					0
RW	70	50	30	10	70	50	30	10		50	30	10		50	30	10		50	30	10
RCR																				
0	119	119	119	119	116	116	116	116		111	111	111		106	106	106		102	102	102
1	111	107	104	101	109	105	102	99		101	99	96		97	95	93		94	92	91
2	103	96	91	86	100	94	89	85		91	87	83		88	84	81		85	82	79
3	95	86	79	74	93	85	78	73		82	76	72		79	75	71		77	73	70
4	88	78	70	64	86	77	69	64		74	68	63		72	67	62		70	65	62
5	82	71	63	57	80	70	62	57		67	61	56		66	60	55		64	59	55
6	76	64	56	51	74	63	56	51		62	55	50		60	54	50		59	53	49
7	71	59	51	46	70	58	51	45		57	50	45		55	49	45		54	49	45
8	67	54	47	41	65	54	46	41		52	46	41		51	45	41		50	45	41
9	63	50	43	38	61	50	43	38		49	42	38		48	42	37		47	41	37
10	59	47	40	35	58	46	39	35		45	39	35		45	39	34		44	38	34

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P205448

CATALOG NUMBER: LD6B60D010TE EU6B60708040 6LBSLI1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	387.8	5.8
10°-20°	987.3	14.8
20°-30°	1259.0	18.9
30°-40°	1305.6	19.6
40°-50°	1203.1	18.0
50°-60°	905.0	13.6
60°-70°	488.5	7.3
70°-80°	131.1	2.0
80°-90°	1.9	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2634.1	39.5
0°-40°	3939.7	59.1
0°-60°	6047.7	90.7
0°-90°	6669.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	6669.2	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	4209	
5°	4145	388
15°	3521	987
25°	2735	1259
35°	2083	1306
45°	1566	1203
55°	1013	905
65°	489	488
75°	113	131
85°	0	2
90°	0	



TEST NUMBER: P205448

CATALOG NUMBER: LD6B60D010TE EU6B60708040 6LBSLI1

CANDELA DISTRIBUTION (FULL):

0°	
0°	4208.6
2.5°	4194.4
5°	4144.8
7.5°	4052.7
10°	3889.7
12.5°	3726.8
15°	3521.3
17.5°	3330.0
20°	3131.6
22.5°	2926.2
25°	2734.9
27.5°	2550.6
30°	2380.6
32.5°	2224.7
35°	2083.0
37.5°	1948.4
40°	1820.9
42.5°	1686.3
45°	1565.8
47.5°	1431.2
50°	1296.6
52.5°	1154.9
55°	1013.2
57.5°	871.5
60°	736.9
62.5°	609.3
65°	488.9
67.5°	375.5
70°	276.3
72.5°	191.3
75°	113.4
77.5°	49.6
80°	14.2
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)