

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P205043

Luminaire Tested: **LD6B60D010TE EU6B60708050 6LBCSMMS1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P205043
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD6B60D010TE EU6B60708050 6LBCSMMS1
Description: PORTFOLIO 6 INCH SHALLOW RECESSED DOWNLIGHT
SHALLOW DISTRIBUTION WITH CAST MATTE METALLIC SILVER TRIM
SINGLE DRIVER D010TE
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 6358.7 lumens
Efficiency: N/A
Efficacy: 101.8 lumens/watt
Spacing Criteria (0/90/45): 1.16 / 1.16 / 1.27
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 62.48
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P205043

CATALOG NUMBER: LD6B60D010TE EU6B60708050 6LBCSMMS1

Luminous Intensity Polar Plot





TEST NUMBER: P205043

CATALOG NUMBER: LD6B60D010TE EU6B60708050 6LBCSMMS1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20					20					20					20
RC	80				70					50					30					0
RW	70	50	30	10	70	50	30	10		50	30	10		50	30	10		50	30	10
RCR																				
0	119	119	119	119	116	116	116	116		111	111	111		106	106	106		102	102	102
1	111	107	103	100	108	105	101	98		100	98	95		97	94	92		93	91	90
2	102	95	89	84	99	93	88	83		90	85	81		86	83	79		83	80	78
3	94	85	77	72	92	83	76	71		80	74	70		77	73	69		75	71	67
4	87	76	68	62	84	74	67	61		72	66	61		70	64	60		68	63	59
5	80	68	60	54	78	67	59	54		65	58	53		63	57	53		61	56	52
6	74	62	54	48	72	61	53	47		59	52	47		58	51	47		56	51	46
7	69	56	48	42	67	56	48	42		54	47	42		53	46	42		51	46	41
8	64	52	44	38	63	51	43	38		50	43	38		48	42	38		47	42	37
9	60	48	40	35	59	47	40	34		46	39	34		45	39	34		44	38	34
10	57	44	36	31	55	43	36	31		43	36	31		42	35	31		41	35	31

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P205043

CATALOG NUMBER: LD6B60D010TE EU6B60708050 6LBCSMMS1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	275.2	4.3
10°-20°	772.2	12.1
20°-30°	1127.8	17.7
30°-40°	1289.9	20.3
40°-50°	1239.7	19.5
50°-60°	957.3	15.1
60°-70°	534.3	8.4
70°-80°	155.5	2.4
80°-90°	6.7	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2175.2	34.2
0°-40°	3465.1	54.5
0°-60°	5662.2	89.0
0°-90°	6358.7	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	6358.7	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2920	
5°	2895	275
15°	2739	772
25°	2451	1128
35°	2065	1290
45°	1616	1240
55°	1073	957
65°	535	534
75°	136	156
85°	4	7
90°	0	



TEST NUMBER: P205043

CATALOG NUMBER: LD6B60D010TE EU6B60708050 6LBCSMMS1

CANDELA DISTRIBUTION (FULL):

0°	
0°	2920.1
2.5°	2920.1
5°	2895.4
7.5°	2883.1
10°	2841.9
12.5°	2792.6
15°	2739.1
17.5°	2685.7
20°	2607.5
22.5°	2545.8
25°	2451.2
27.5°	2356.6
30°	2262.0
32.5°	2167.4
35°	2064.6
37.5°	1961.8
40°	1842.5
42.5°	1735.6
45°	1616.3
47.5°	1480.6
50°	1353.1
52.5°	1213.3
55°	1073.4
57.5°	929.5
60°	793.8
62.5°	658.0
65°	534.7
67.5°	419.5
70°	312.6
72.5°	218.0
75°	135.7
77.5°	69.9
80°	24.7
82.5°	8.2
85°	4.1
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)