

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P205558

Luminaire Tested: **LD6B60D010TE EU6B60709050 6LBMGPH1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P205558
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD6B60D010TE EU6B60709050 6LBMGPH1
Description: PORTFOLIO 6 INCH 50 DEGREE CUTOFF RECESSED DOWNLIGHT
MEDIUM DISTRIBUTION WITH GRAPHITE HAZE TRIM
SINGLE DRIVER D010TE
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 2904.0 lumens
Efficiency: N/A
Efficacy: 46.5 lumens/watt
Spacing Criteria (0/90/45): 0.94 / 0.94 / 0.91
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 62.48
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P205558

CATALOG NUMBER: LD6B60D010TE EU6B60709050 6LBMGPH1

Luminous Intensity Polar Plot





TEST NUMBER: P205558

CATALOG NUMBER: LD6B60D010TE EU6B60709050 6LBMGPH1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20
RC	80					70					50					30					10
RW	70	50	30	10		70	50	30	10		50	30	10		50	30	10		50	30	10
RCR																					
0	119	119	119	119		116	116	116	116		111	111	111		106	106	106		102	102	102
1	113	110	108	105		111	108	106	104		104	102	101		100	99	98		97	96	95
2	107	102	98	94		105	100	97	93		97	94	91		94	92	89		91	89	87
3	102	95	90	85		100	93	89	85		91	87	83		88	85	82		86	83	81
4	96	88	82	78		94	87	82	77		85	80	77		83	79	76		81	78	75
5	91	82	76	72		89	81	76	71		79	74	71		78	73	70		76	72	69
6	86	77	71	66		85	76	70	66		74	69	65		73	68	65		72	68	64
7	82	72	66	61		80	71	65	61		70	65	61		69	64	60		68	63	60
8	77	68	61	57		76	67	61	57		66	60	57		65	60	56		64	59	56
9	74	64	57	53		72	63	57	53		62	57	53		61	56	53		60	56	53
10	70	60	54	50		69	59	54	50		59	53	50		58	53	49		57	53	49

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P205558

CATALOG NUMBER: LD6B60D010TE EU6B60709050 6LBMGPH1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	278.0	9.6
10°-20°	721.3	24.8
20°-30°	919.1	31.6
30°-40°	649.5	22.4
40°-50°	237.1	8.2
50°-60°	65.7	2.3
60°-70°	23.9	0.8
70°-80°	8.5	0.3
80°-90°	0.8	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1918.4	66.1
0°-40°	2567.9	88.4
0°-60°	2870.8	98.9
0°-90°	2904.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2904.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	3026	
5°	2973	278
15°	2569	721
25°	2041	919
35°	1032	650
45°	287	237
55°	70	66
65°	24	24
75°	6	9
85°	0	1
90°	0	



TEST NUMBER: P205558

CATALOG NUMBER: LD6B60D010TE EU6B60709050 6LBMGPH1

CANDELA DISTRIBUTION (FULL):

	0°
0°	3026.1
2.5°	3014.3
5°	2973.3
7.5°	2891.2
10°	2803.2
12.5°	2685.9
15°	2568.6
17.5°	2451.3
20°	2334.0
22.5°	2193.3
25°	2040.8
27.5°	1829.7
30°	1595.1
32.5°	1313.6
35°	1032.1
37.5°	785.8
40°	574.7
42.5°	416.4
45°	287.4
47.5°	193.5
50°	129.0
52.5°	88.0
55°	70.4
57.5°	52.8
60°	41.1
62.5°	29.3
65°	23.5
67.5°	17.6
70°	11.7
72.5°	11.7
75°	5.9
77.5°	5.9
80°	5.9
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)