

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P204541

Luminaire Tested: **LD6B70D010TE EU6B60709024 6LBSB1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P204541
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD6B70D010TE EU6B60709024 6LBSB1
Description: PORTFOLIO 6 INCH SHALLOW RECESSED DOWNLIGHT
SHALLOW DISTRIBUTION WITH SPECULAR BLACK TRIM
SINGLE DRIVER D010TE
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 4688.4 lumens
Efficiency: N/A
Efficacy: 59.0 lumens/watt
Spacing Criteria (0/90/45): 1.2 / 1.2 / 1.3
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 79.45
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P204541

CATALOG NUMBER: LD6B70D010TE EU6B60709024 6LBSB1

Luminous Intensity Polar Plot





TEST NUMBER: P204541

CATALOG NUMBER: LD6B70D010TE EU6B60709024 6LBSB1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			100																
1	111	107	103	100	108	105	101	98	100	98	95	97	94	93	93	91	90	88			88																
2	102	95	89	84	100	93	88	83	90	85	81	86	83	79	84	80	78	76			76																
3	94	84	77	72	91	83	76	71	80	74	70	77	73	68	75	71	67	65			65																
4	86	76	68	62	84	74	67	61	72	65	60	70	64	60	68	63	59	57			57																
5	80	68	60	54	78	67	59	53	65	58	53	63	57	52	61	56	52	50			50																
6	74	62	53	47	72	61	53	47	59	52	47	57	51	46	56	50	46	44			44																
7	69	56	48	42	67	55	48	42	54	47	42	52	46	41	51	45	41	39			39																
8	64	51	43	38	63	51	43	38	49	42	37	48	42	37	47	41	37	35			35																
9	60	47	39	34	59	47	39	34	46	39	34	45	38	34	44	38	34	32			32																
10	56	44	36	31	55	43	36	31	42	36	31	41	35	31	40	35	31	29			29																

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P204541

CATALOG NUMBER: LD6B70D010TE EU6B60709024 6LBSB1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	195.2	4.2
10°-20°	553.9	11.8
20°-30°	823.9	17.6
30°-40°	958.8	20.4
40°-50°	934.5	19.9
50°-60°	718.8	15.3
60°-70°	397.3	8.5
70°-80°	105.2	2.2
80°-90°	0.8	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1573.0	33.6
0°-40°	2531.8	54.0
0°-60°	4185.1	89.3
0°-90°	4688.4	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	4688.4	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2068	
5°	2056	195
15°	1961	554
25°	1789	824
35°	1539	959
45°	1212	935
55°	802	719
65°	398	397
75°	89	105
85°	0	1
90°	0	



TEST NUMBER: P204541

CATALOG NUMBER: LD6B70D010TE EU6B60709024 6LBSB1

CANDELA DISTRIBUTION (FULL):

	0°
0°	2068.2
2.5°	2068.2
5°	2056.3
7.5°	2038.5
10°	2026.6
12.5°	1991.0
15°	1961.3
17.5°	1931.5
20°	1889.9
22.5°	1848.3
25°	1788.9
27.5°	1729.5
30°	1670.0
32.5°	1604.7
35°	1539.3
37.5°	1456.1
40°	1384.8
42.5°	1307.5
45°	1212.4
47.5°	1123.3
50°	1022.2
52.5°	915.3
55°	802.3
57.5°	695.4
60°	594.3
62.5°	493.3
65°	398.2
67.5°	309.0
70°	225.8
72.5°	154.5
75°	89.1
77.5°	41.6
80°	5.9
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)