

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P204847

Luminaire Tested: **LD6B70D010TE EU6B60708027 6LBCSMW1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P204847
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD6B70D010TE EU6B60708027 6LBCSMW1
Description: PORTFOLIO 6 INCH SHALLOW RECESSED DOWNLIGHT
SHALLOW DISTRIBUTION WITH CAST MATTE WHITE TRIM
SINGLE DRIVER D010TE
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 7446.9 lumens
Efficiency: N/A
Efficacy: 93.7 lumens/watt
Spacing Criteria (0/90/45): 1.23 / 1.23 / 1.33
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 79.45
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P204847

CATALOG NUMBER: LD6B70D010TE EU6B60708027 6LBCSMW1

Luminous Intensity Polar Plot





TEST NUMBER: P204847

CATALOG NUMBER: LD6B70D010TE EU6B60708027 6LBSCMW1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

| | | | | | | | | | | | | | | | | | | | | | | |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|----|-----|
| RF | 20 | | | | 20 | | | | 20 | | | | 20 | | | | 20 | | | | 20 | |
| RC | 80 | | | | 70 | | | | 50 | | | | 30 | | | | 10 | | | | 0 | |
| RW | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 0 | |
| RCR | | | | | | | | | | | | | | | | | | | | | | |
| 0 | 119 | 119 | 119 | 119 | 116 | 116 | 116 | 116 | 111 | 111 | 111 | 106 | 106 | 106 | 102 | 102 | 102 | 100 | | | | 100 |
| 1 | 110 | 106 | 102 | 99 | 108 | 104 | 100 | 97 | 100 | 97 | 94 | 96 | 93 | 91 | 92 | 90 | 89 | 87 | | | | 87 |
| 2 | 101 | 94 | 87 | 82 | 99 | 92 | 86 | 81 | 88 | 84 | 79 | 85 | 81 | 78 | 82 | 79 | 76 | 74 | | | | 74 |
| 3 | 93 | 83 | 75 | 70 | 90 | 81 | 74 | 69 | 79 | 73 | 68 | 76 | 71 | 67 | 73 | 69 | 65 | 63 | | | | 63 |
| 4 | 85 | 74 | 66 | 60 | 83 | 73 | 65 | 59 | 70 | 64 | 58 | 68 | 62 | 58 | 66 | 61 | 57 | 55 | | | | 55 |
| 5 | 79 | 66 | 58 | 52 | 77 | 65 | 57 | 51 | 63 | 56 | 51 | 61 | 55 | 50 | 60 | 54 | 50 | 48 | | | | 48 |
| 6 | 73 | 60 | 52 | 45 | 71 | 59 | 51 | 45 | 57 | 50 | 45 | 56 | 49 | 44 | 54 | 49 | 44 | 42 | | | | 42 |
| 7 | 68 | 55 | 46 | 40 | 66 | 54 | 46 | 40 | 52 | 45 | 40 | 51 | 44 | 40 | 50 | 44 | 39 | 37 | | | | 37 |
| 8 | 63 | 50 | 42 | 36 | 61 | 49 | 41 | 36 | 48 | 41 | 36 | 47 | 40 | 36 | 46 | 40 | 35 | 33 | | | | 33 |
| 9 | 59 | 46 | 38 | 33 | 57 | 45 | 38 | 32 | 44 | 37 | 32 | 43 | 37 | 32 | 42 | 36 | 32 | 30 | | | | 30 |
| 10 | 55 | 42 | 35 | 30 | 54 | 42 | 34 | 30 | 41 | 34 | 29 | 40 | 34 | 29 | 39 | 33 | 29 | 27 | | | | 27 |

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P204847

CATALOG NUMBER: LD6B70D010TE EU6B60708027 6LBCSMW1

ZONAL LUMENS:

| Zone | Lumens | % Fixture |
|-----------|--------|-----------|
| 0°-10° | 288.2 | 3.9 |
| 10°-20° | 820.4 | 11.0 |
| 20°-30° | 1234.1 | 16.6 |
| 30°-40° | 1462.6 | 19.6 |
| 40°-50° | 1455.5 | 19.5 |
| 50°-60° | 1173.4 | 15.8 |
| 60°-70° | 709.8 | 9.5 |
| 70°-80° | 263.5 | 3.5 |
| 80°-90° | 39.3 | 0.5 |
| 90°-100° | 0.0 | 0.0 |
| 100°-110° | 0.0 | 0.0 |
| 110°-120° | 0.0 | 0.0 |
| 120°-130° | 0.0 | 0.0 |
| 130°-140° | 0.0 | 0.0 |
| 140°-150° | 0.0 | 0.0 |
| 150°-160° | 0.0 | 0.0 |
| 160°-170° | 0.0 | 0.0 |
| 170°-180° | 0.0 | 0.0 |
| 0°-30° | 2342.7 | 31.5 |
| 0°-40° | 3805.3 | 51.1 |
| 0°-60° | 6434.2 | 86.4 |
| 0°-90° | 7446.9 | 100.0 |
| 90°-120° | 0.0 | 0.0 |
| 90°-150° | 0.0 | 0.0 |
| 90°-180° | 0.0 | 0.0 |
| 0°-180° | 7446.9 | 100.0 |

CANDELA DISTRIBUTION:

| | 0° | Flux |
|-----|------|------|
| 0° | 3042 | |
| 5° | 3028 | 288 |
| 15° | 2906 | 820 |
| 25° | 2680 | 1234 |
| 35° | 2342 | 1463 |
| 45° | 1895 | 1456 |
| 55° | 1309 | 1173 |
| 65° | 713 | 710 |
| 75° | 239 | 264 |
| 85° | 32 | 39 |
| 90° | 0 | |



TEST NUMBER: P204847

CATALOG NUMBER: LD6B70D010TE EU6B60708027 6LBCSMW1

CANDELA DISTRIBUTION (FULL):

| | 0° |
|-------|--------|
| 0° | 3041.5 |
| 2.5° | 3041.5 |
| 5° | 3028.0 |
| 7.5° | 3019.0 |
| 10° | 2991.9 |
| 12.5° | 2946.8 |
| 15° | 2906.1 |
| 17.5° | 2861.0 |
| 20° | 2806.9 |
| 22.5° | 2752.7 |
| 25° | 2680.5 |
| 27.5° | 2603.8 |
| 30° | 2518.1 |
| 32.5° | 2436.8 |
| 35° | 2342.1 |
| 37.5° | 2242.8 |
| 40° | 2125.5 |
| 42.5° | 2012.6 |
| 45° | 1895.3 |
| 47.5° | 1764.4 |
| 50° | 1620.0 |
| 52.5° | 1471.1 |
| 55° | 1308.7 |
| 57.5° | 1164.3 |
| 60° | 1001.8 |
| 62.5° | 857.4 |
| 65° | 713.0 |
| 67.5° | 577.6 |
| 70° | 451.3 |
| 72.5° | 338.4 |
| 75° | 239.2 |
| 77.5° | 153.4 |
| 80° | 90.3 |
| 82.5° | 54.2 |
| 85° | 31.6 |
| 87.5° | 13.5 |
| 90° | 0.0 |



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)