

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P204130

Luminaire Tested: **LD6B70D010TE EU6B60709027 6LBNMW1**

Issue Date: 3/3/2020

**Test Information**

Test Method: LM-41-14  
Report Number: P204130  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)  
Test Lab: INNOVATION CENTER-P3  
Issue Date: 3/3/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: io LED  
Catalog Number: LD6B70D010TE EU6B60709027 6LBNMW1  
Description: PORTFOLIO 6 INCH 50 DEGREE CUTOFF RECESSED DOWNLIGHT  
NARROW DISTRIBUTION WITH MATTE WHITE TRIM  
SINGLE DRIVER D010TE  
Light Source: HIGH LUMEN LED  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 4202.1 lumens  
Efficiency: N/A  
Efficacy: 52.9 lumens/watt  
Spacing Criteria (0/90/45): 0.99 / 0.99 / 0.97  
Luminous Opening: Point Source (0' x 0' x 0')  
CIE Type: Direct


Input Watts (W): 79.45  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P204130

CATALOG NUMBER: LD6B70D010TE EU6B60709027 6LBNMW1

### Luminous Intensity Polar Plot





TEST NUMBER: P204130

CATALOG NUMBER: LD6B70D010TE EU6B60709027 6LBNMW1

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	112	108	105	103	109	106	103	101	102	100	98	98	97	95	95	93	92	90			
2	105	99	94	90	102	97	92	89	94	90	87	91	87	85	88	85	83	81			
3	98	90	84	79	96	89	83	79	86	81	77	84	80	76	81	78	75	73			
4	92	83	76	71	90	82	76	71	80	74	70	77	73	69	75	71	68	66			
5	87	77	70	64	85	76	69	64	74	68	64	72	67	63	70	66	62	61			
6	81	71	64	59	80	70	63	59	68	63	58	67	62	58	66	61	57	56			
7	77	66	59	54	75	65	59	54	64	58	54	63	57	53	61	57	53	51			
8	72	61	55	50	71	61	54	50	60	54	49	59	53	49	58	53	49	47			
9	69	58	51	46	67	57	51	46	56	50	46	55	50	46	54	49	46	44			
10	65	54	47	43	64	54	47	43	53	47	43	52	46	43	51	46	43	41			

**AVERAGE LUMINANCE (cd/sqm):**





TEST NUMBER: P204130

CATALOG NUMBER: LD6B70D010TE EU6B60709027 6LBNMW1

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	320.0	7.6
10°-20°	848.2	20.2
20°-30°	1132.5	26.9
30°-40°	913.6	21.7
40°-50°	437.9	10.4
50°-60°	259.6	6.2
60°-70°	172.5	4.1
70°-80°	92.4	2.2
80°-90°	25.4	0.6
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2300.7	54.8
0°-40°	3214.3	76.5
0°-60°	3911.7	93.1
0°-90°	4202.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	4202.1	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	3446	
5°	3406	320
15°	3019	848
25°	2478	1132
35°	1463	914
45°	541	438
55°	287	260
65°	174	173
75°	87	92
85°	20	25
90°	0	



TEST NUMBER: P204130

CATALOG NUMBER: LD6B70D010TE EU6B60709027 6LBNMW1

**CANDELA DISTRIBUTION (FULL):**

0°	
0°	3446.2
2.5°	3446.2
5°	3406.1
7.5°	3339.3
10°	3245.8
12.5°	3145.6
15°	3018.7
17.5°	2898.5
20°	2765.0
22.5°	2624.7
25°	2477.8
27.5°	2324.2
30°	2103.8
32.5°	1796.6
35°	1462.6
37.5°	1155.4
40°	894.9
42.5°	694.6
45°	541.0
47.5°	427.4
50°	360.6
52.5°	320.6
55°	287.2
57.5°	260.5
60°	227.1
62.5°	200.4
65°	173.6
67.5°	146.9
70°	126.9
72.5°	106.9
75°	86.8
77.5°	66.8
80°	53.4
82.5°	40.1
85°	20.0
87.5°	6.7
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093







— 0°-180°







(END OF REPORT)