

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P204233

Luminaire Tested: **LD6B70D010TE EU6B60709027 6LBSH1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P204233
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD6B70D010TE EU6B60709027 6LBSH1
Description: PORTFOLIO 6 INCH SHALLOW RECESSED DOWNLIGHT
SHALLOW DISTRIBUTION WITH SEMI-SPECULAR CLEAR TRIM
SINGLE DRIVER D010TE
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 6063.0 lumens
Efficiency: N/A
Efficacy: 76.3 lumens/watt
Spacing Criteria (0/90/45): 1.06 / 1.06 / 1.17
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 79.45
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P204233

CATALOG NUMBER: LD6B70D010TE EU6B60709027 6LBSH1

Luminous Intensity Polar Plot





TEST NUMBER: P204233

CATALOG NUMBER: LD6B70D010TE EU6B60709027 6LBSH1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	111	107	104	101	108	105	102	99	101	98	96	97	95	93	93	92	90	88			
2	102	96	90	85	100	94	88	84	90	86	82	87	83	80	84	81	79	77			
3	95	85	78	73	92	84	77	72	81	75	71	78	74	70	76	72	69	67			
4	87	77	69	63	85	75	68	63	73	67	62	71	65	61	69	64	60	58			
5	81	69	61	55	79	68	61	55	66	60	55	64	59	54	63	58	53	51			
6	75	63	55	49	73	62	54	49	60	54	49	59	53	48	57	52	48	46			
7	70	58	50	44	68	57	49	44	55	49	44	54	48	43	53	47	43	41			
8	65	53	45	40	64	52	45	40	51	44	39	50	44	39	49	43	39	37			
9	61	49	41	36	60	48	41	36	47	40	36	46	40	36	45	40	35	34			
10	58	45	38	33	56	45	38	33	44	37	33	43	37	33	42	37	33	31			

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P204233

CATALOG NUMBER: LD6B70D010TE EU6B60709027 6LBSH1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	297.0	4.9
10°-20°	807.3	13.3
20°-30°	1121.1	18.5
30°-40°	1223.4	20.2
40°-50°	1141.3	18.8
50°-60°	866.2	14.3
60°-70°	474.3	7.8
70°-80°	130.5	2.2
80°-90°	1.8	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2225.4	36.7
0°-40°	3448.9	56.9
0°-60°	5456.4	90.0
0°-90°	6063.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	6063.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	3171	
5°	3144	297
15°	2877	807
25°	2437	1121
35°	1956	1223
45°	1482	1141
55°	968	866
65°	474	474
75°	114	131
85°	0	2
90°	0	



TEST NUMBER: P204233

CATALOG NUMBER: LD6B70D010TE EU6B60709027 6LBSH1

CANDELA DISTRIBUTION (FULL):

0°	
0°	3171.0
2.5°	3171.0
5°	3144.3
7.5°	3104.2
10°	3044.1
12.5°	2964.0
15°	2877.2
17.5°	2770.4
20°	2670.3
22.5°	2550.1
25°	2436.6
27.5°	2323.1
30°	2196.3
32.5°	2076.1
35°	1956.0
37.5°	1835.8
40°	1722.3
42.5°	1602.2
45°	1482.0
47.5°	1361.8
50°	1228.3
52.5°	1101.5
55°	968.0
57.5°	841.1
60°	714.3
62.5°	587.5
65°	474.0
67.5°	367.2
70°	273.7
72.5°	186.9
75°	113.5
77.5°	53.4
80°	13.4
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)