

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P204125

Luminaire Tested: **LD6B70D010TE EU6B60708030 6LBNMW1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P204125
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD6B70D010TE EU6B60708030 6LBNMW1
Description: PORTFOLIO 6 INCH 50 DEGREE CUTOFF RECESSED DOWNLIGHT
NARROW DISTRIBUTION WITH MATTE WHITE TRIM
SINGLE DRIVER D010TE
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 5115.8 lumens
Efficiency: N/A
Efficacy: 64.4 lumens/watt
Spacing Criteria (0/90/45): 0.99 / 0.99 / 0.97
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 79.45
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P204125

CATALOG NUMBER: LD6B70D010TE EU6B60708030 6LBNMW1

Luminous Intensity Polar Plot





TEST NUMBER: P204125

CATALOG NUMBER: LD6B70D010TE EU6B60708030 6LBNMW1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	112	108	105	103	109	106	103	101	102	100	98	98	97	95	95	93	92	90			
2	105	99	94	90	102	97	92	89	94	90	87	91	87	85	88	85	83	81			
3	98	90	84	79	96	89	83	79	86	81	77	84	80	76	81	78	75	73			
4	92	83	76	71	90	82	76	71	80	74	70	77	73	69	75	71	68	66			
5	87	77	70	65	85	76	69	64	74	68	64	72	67	63	70	66	62	61			
6	81	71	64	59	80	70	63	59	68	63	58	67	62	58	66	61	57	56			
7	77	66	59	54	75	65	59	54	64	58	54	63	57	53	61	57	53	51			
8	72	61	55	50	71	61	54	50	60	54	49	59	53	49	58	53	49	47			
9	69	58	51	46	67	57	51	46	56	50	46	55	50	46	54	49	46	44			
10	65	54	47	43	64	54	47	43	53	47	43	52	46	43	51	46	43	41			

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P204125

CATALOG NUMBER: LD6B70D010TE EU6B60708030 6LBNMW1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	389.6	7.6
10°-20°	1032.7	20.2
20°-30°	1378.7	26.9
30°-40°	1112.3	21.7
40°-50°	533.1	10.4
50°-60°	316.0	6.2
60°-70°	210.1	4.1
70°-80°	112.5	2.2
80°-90°	30.9	0.6
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2801.0	54.8
0°-40°	3913.2	76.5
0°-60°	4762.3	93.1
0°-90°	5115.8	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	5115.8	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	4196	
5°	4147	390
15°	3675	1033
25°	3017	1379
35°	1781	1112
45°	659	533
55°	350	316
65°	211	210
75°	106	113
85°	24	31
90°	0	



TEST NUMBER: P204125

CATALOG NUMBER: LD6B70D010TE EU6B60708030 6LBNMW1

CANDELA DISTRIBUTION (FULL):

	0°
0°	4195.6
2.5°	4195.6
5°	4146.8
7.5°	4065.5
10°	3951.6
12.5°	3829.7
15°	3675.2
17.5°	3528.8
20°	3366.2
22.5°	3195.4
25°	3016.6
27.5°	2829.6
30°	2561.2
32.5°	2187.2
35°	1780.7
37.5°	1406.6
40°	1089.5
42.5°	845.6
45°	658.6
47.5°	520.4
50°	439.1
52.5°	390.3
55°	349.6
57.5°	317.1
60°	276.5
62.5°	243.9
65°	211.4
67.5°	178.9
70°	154.5
72.5°	130.1
75°	105.7
77.5°	81.3
80°	65.0
82.5°	48.8
85°	24.4
87.5°	8.1
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)