

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P202591

Luminaire Tested: **LD6B70D010TE EU6B60709730 6LBSWMH1**

Issue Date: 3/3/2020

**Test Information**

Test Method: LM-41-14  
Report Number: P202591  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)  
Test Lab: INNOVATION CENTER-P3  
Issue Date: 3/3/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: io LED  
Catalog Number: LD6B70D010TE EU6B60709730 6LBSWMH1  
Description: PORTFOLIO 6 INCH SHALLOW RECESSED DOWNLIGHT  
SHALLOW DISTRIBUTION WITH WARM HAZE TRIM  
SINGLE DRIVER D010TE  
Light Source: HIGH LUMEN LED  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 5560.5 lumens  
Efficiency: N/A  
Efficacy: 70.0 lumens/watt  
Spacing Criteria (0/90/45): 0.97 / 0.97 / 1.1  
Luminous Opening: Point Source (0' x 0' x 0')  
CIE Type: Direct


Input Watts (W): 79.45  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P202591

CATALOG NUMBER: LD6B70D010TE EU6B60709730 6LBSWMH1

### Luminous Intensity Polar Plot





TEST NUMBER: P202591

CATALOG NUMBER: LD6B70D010TE EU6B60709730 6LBSWMH1

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20				20	
RC	80				70				50				30				10				0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0	
RCR																						
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100				100
1	111	107	104	101	108	105	102	99	101	98	96	97	95	93	94	92	90	88				88
2	103	96	90	85	100	94	89	84	91	86	82	87	84	81	84	81	79	77				77
3	95	86	79	73	92	84	78	73	81	76	71	79	74	70	76	72	69	67				67
4	88	77	70	64	86	76	69	63	74	67	62	71	66	62	69	65	61	59				59
5	81	70	62	56	79	69	61	56	67	60	55	65	59	55	63	58	54	52				52
6	76	64	56	50	74	63	55	50	61	54	49	59	53	49	58	53	48	47				47
7	70	58	50	45	69	57	50	45	56	49	44	55	48	44	53	48	44	42				42
8	66	54	46	40	64	53	45	40	52	45	40	50	44	40	49	44	40	38				38
9	62	49	42	37	61	49	42	37	48	41	37	47	41	36	46	40	36	35				35
10	58	46	39	34	57	45	38	34	45	38	34	44	38	33	43	37	33	32				32

**AVERAGE LUMINANCE (cd/sqm):**





TEST NUMBER: P202591

CATALOG NUMBER: LD6B70D010TE EU6B60709730 6LBSWMH1

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	297.5	5.3
10°-20°	777.7	14.0
20°-30°	1031.2	18.5
30°-40°	1099.9	19.8
40°-50°	1028.1	18.5
50°-60°	784.0	14.1
60°-70°	426.5	7.7
70°-80°	114.4	2.1
80°-90°	1.4	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2106.3	37.9
0°-40°	3206.2	57.7
0°-60°	5018.3	90.2
0°-90°	5560.5	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	5560.5	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	3215	
5°	3171	297
15°	2773	778
25°	2245	1031
35°	1758	1100
45°	1339	1028
55°	882	784
65°	426	426
75°	99	114
85°	0	1
90°	0	



TEST NUMBER: P202591

CATALOG NUMBER: LD6B70D010TE EU6B60709730 6LBSWMH1

**CANDELA DISTRIBUTION (FULL):**

0°	
0°	3215.4
2.5°	3205.2
5°	3171.1
7.5°	3099.6
10°	3017.8
12.5°	2902.0
15°	2772.6
17.5°	2643.2
20°	2503.5
22.5°	2370.7
25°	2244.6
27.5°	2111.8
30°	1985.8
32.5°	1863.2
35°	1757.6
37.5°	1652.0
40°	1543.0
42.5°	1444.2
45°	1338.6
47.5°	1222.8
50°	1113.8
52.5°	998.0
55°	882.2
57.5°	756.2
60°	640.4
62.5°	531.4
65°	425.8
67.5°	330.4
70°	241.8
72.5°	166.9
75°	98.8
77.5°	44.3
80°	10.2
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093







— 0°-180°







(END OF REPORT)