

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P203611

Luminaire Tested: **LD6B70D010TE EU6B60708035 6LBMMW1**

Issue Date: 3/3/2020

**Test Information**

Test Method: LM-41-14  
Report Number: P203611  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)  
Test Lab: INNOVATION CENTER-P3  
Issue Date: 3/3/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: io LED  
Catalog Number: LD6B70D010TE EU6B60708035 6LBMMW1  
Description: PORTFOLIO 6 INCH 50 DEGREE CUTOFF RECESSED DOWNLIGHT  
MEDIUM DISTRIBUTION WITH MATTE WHITE TRIM  
SINGLE DRIVER D010TE  
Light Source: HIGH LUMEN LED  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 5830.0 lumens  
Efficiency: N/A  
Efficacy: 73.4 lumens/watt  
Spacing Criteria (0/90/45): 1 / 1 / 0.97  
Luminous Opening: Point Source (0' x 0' x 0')  
CIE Type: Direct


Input Watts (W): 79.45  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P203611

CATALOG NUMBER: LD6B70D010TE EU6B60708035 6LBMMW1

### Luminous Intensity Polar Plot





TEST NUMBER: P203611

CATALOG NUMBER: LD6B70D010TE EU6B60708035 6LBMMW1

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			100
1	111	108	104	101	109	105	103	100	101	99	97	98	96	94	94	92	91	89			89
2	104	97	92	88	101	96	91	87	92	88	85	89	86	83	86	83	81	79			79
3	97	88	82	77	95	87	81	76	84	79	75	82	77	74	79	76	73	71			71
4	90	81	74	68	88	80	73	68	77	72	67	75	70	66	73	69	65	64			64
5	85	74	67	61	83	73	66	61	71	65	61	69	64	60	68	63	59	58			58
6	79	68	61	56	78	68	61	56	66	60	55	64	59	55	63	58	54	53			53
7	75	63	56	51	73	63	56	51	61	55	50	60	54	50	59	54	50	48			48
8	70	59	52	47	69	58	51	47	57	51	46	56	50	46	55	50	46	44			44
9	66	55	48	43	65	54	48	43	53	47	43	52	47	43	51	46	43	41			41
10	63	51	45	40	62	51	44	40	50	44	40	49	44	40	48	43	40	38			38

**AVERAGE LUMINANCE (cd/sqm):**





TEST NUMBER: P203611

CATALOG NUMBER: LD6B70D010TE EU6B60708035 6LBMMW1

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	401.8	6.9
10°-20°	1076.4	18.5
20°-30°	1445.3	24.8
30°-40°	1185.5	20.3
40°-50°	711.9	12.2
50°-60°	473.1	8.1
60°-70°	317.1	5.4
70°-80°	170.7	2.9
80°-90°	48.1	0.8
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2923.5	50.1
0°-40°	4109.0	70.5
0°-60°	5294.1	90.8
0°-90°	5830.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	5830.0	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	4350	
5°	4278	402
15°	3836	1076
25°	3184	1445
35°	1882	1186
45°	901	712
55°	523	473
65°	322	317
75°	161	171
85°	40	48
90°	0	



TEST NUMBER: P203611

CATALOG NUMBER: LD6B70D010TE EU6B60708035 6LBMMW1

**CANDELA DISTRIBUTION (FULL):**

0°	
0°	4350.1
2.5°	4317.9
5°	4277.7
7.5°	4189.3
10°	4084.8
12.5°	3956.1
15°	3835.5
17.5°	3690.7
20°	3546.0
22.5°	3385.2
25°	3184.2
27.5°	2943.0
30°	2621.3
32.5°	2259.5
35°	1881.6
37.5°	1559.9
40°	1286.5
42.5°	1069.4
45°	900.6
47.5°	763.9
50°	667.4
52.5°	587.0
55°	522.7
57.5°	466.4
60°	418.1
62.5°	361.8
65°	321.6
67.5°	273.4
70°	233.2
72.5°	193.0
75°	160.8
77.5°	128.7
80°	96.5
82.5°	72.4
85°	40.2
87.5°	16.1
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093







— 0°-180°







(END OF REPORT)