

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P205156

Luminaire Tested: **LD6B70D010TE EU6B60708040 6LBMLI1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P205156
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD6B70D010TE EU6B60708040 6LBMLI1
Description: PORTFOLIO 6 INCH 50 DEGREE CUTOFF RECESSED DOWNLIGHT
MEDIUM DISTRIBUTION WITH SPECULAR CLEAR TRIM
SINGLE DRIVER D010TE
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 6569.3 lumens
Efficiency: N/A
Efficacy: 82.7 lumens/watt
Spacing Criteria (0/90/45): 0.85 / 0.85 / 0.85
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 79.45
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P205156

CATALOG NUMBER: LD6B70D010TE EU6B60708040 6LBMLI1

Luminous Intensity Polar Plot





TEST NUMBER: P205156

CATALOG NUMBER: LD6B70D010TE EU6B60708040 6LBMLI1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	114	111	109	106	111	109	107	105	105	103	101	101	100	98	98	97	96	94			
2	108	103	100	96	106	102	98	95	99	96	93	96	93	91	93	91	89	88			
3	103	97	92	88	101	95	91	87	93	89	86	90	87	85	88	85	83	82			
4	98	91	85	81	96	89	84	81	87	83	80	85	82	79	83	80	78	76			
5	93	85	79	75	91	84	79	75	82	78	74	81	77	73	79	76	73	71			
6	89	80	74	70	87	79	74	70	78	73	69	76	72	69	75	71	68	67			
7	84	75	69	65	83	75	69	65	73	68	65	72	68	64	71	67	64	63			
8	80	71	65	61	79	70	65	61	69	64	61	68	64	60	67	63	60	59			
9	77	67	61	57	75	67	61	57	66	61	57	65	60	57	64	60	57	55			
10	73	64	58	54	72	63	58	54	62	57	54	62	57	54	61	57	54	52			

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P205156

CATALOG NUMBER: LD6B70D010TE EU6B60708040 6LBMLI1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	757.4	11.5
10°-20°	1885.6	28.7
20°-30°	2191.9	33.4
30°-40°	1342.3	20.4
40°-50°	333.3	5.1
50°-60°	39.0	0.6
60°-70°	14.5	0.2
70°-80°	5.5	0.1
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	4834.8	73.6
0°-40°	6177.1	94.0
0°-60°	6549.3	99.7
0°-90°	6569.3	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	6569.3	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	8221	
5°	8112	757
15°	6767	1886
25°	4850	2192
35°	2102	1342
45°	370	333
55°	34	39
65°	17	14
75°	8	6
85°	0	0
90°	0	



TEST NUMBER: P205156

CATALOG NUMBER: LD6B70D010TE EU6B60708040 6LBML11

CANDELA DISTRIBUTION (FULL):

0°	
0°	8221.3
2.5°	8212.9
5°	8112.0
7.5°	7893.4
10°	7599.2
12.5°	7212.5
15°	6767.0
17.5°	6287.9
20°	5817.1
22.5°	5346.4
25°	4850.4
27.5°	4278.8
30°	3623.1
32.5°	2858.1
35°	2101.6
37.5°	1479.5
40°	1008.7
42.5°	630.5
45°	369.9
47.5°	210.2
50°	109.3
52.5°	50.4
55°	33.6
57.5°	25.2
60°	25.2
62.5°	16.8
65°	16.8
67.5°	8.4
70°	8.4
72.5°	8.4
75°	8.4
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)