

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P203309

Luminaire Tested: **LD6B70D010TE EU6B60709040 6LBMH1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P203309
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD6B70D010TE EU6B60709040 6LBMH1
Description: PORTFOLIO 6 INCH 50 DEGREE CUTOFF RECESSED DOWNLIGHT
MEDIUM DISTRIBUTION WITH SEMI-SPECULAR CLEAR TRIM
SINGLE DRIVER D010TE
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 4495.5 lumens
Efficiency: N/A
Efficacy: 56.6 lumens/watt
Spacing Criteria (0/90/45): 0.94 / 0.94 / 0.93
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 79.45
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P203309

CATALOG NUMBER: LD6B70D010TE EU6B60709040 6LBMH1

Luminous Intensity Polar Plot





TEST NUMBER: P203309

CATALOG NUMBER: LD6B70D010TE EU6B60709040 6LBMH1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	113	110	107	105	111	108	105	103	104	102	100	100	99	97	97	95	94	92			
2	107	102	97	93	105	100	96	92	97	93	90	94	91	88	91	89	87	85			
3	101	94	88	84	99	92	87	84	90	86	82	87	84	81	85	82	80	78			
4	95	87	81	76	93	86	80	76	84	79	75	82	78	74	80	76	73	72			
5	90	81	75	70	88	80	74	70	78	73	69	76	72	68	75	71	68	66			
6	85	75	69	64	83	75	69	64	73	68	64	72	67	63	70	66	63	61			
7	80	70	64	59	79	70	64	59	68	63	59	67	62	59	66	62	58	57			
8	76	66	60	55	75	65	59	55	64	59	55	63	58	55	62	58	54	53			
9	72	62	56	51	71	61	55	51	60	55	51	60	55	51	59	54	51	49			
10	69	58	52	48	68	58	52	48	57	52	48	56	51	48	55	51	48	46			

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P203309

CATALOG NUMBER: LD6B70D010TE EU6B60709040 6LBMH1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	406.8	9.0
10°-20°	1052.3	23.4
20°-30°	1363.5	30.3
30°-40°	1012.3	22.5
40°-50°	427.3	9.5
50°-60°	151.8	3.4
60°-70°	58.6	1.3
70°-80°	20.3	0.5
80°-90°	2.6	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2822.6	62.8
0°-40°	3834.9	85.3
0°-60°	4414.0	98.2
0°-90°	4495.5	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	4495.5	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	4449	
5°	4352	407
15°	3756	1052
25°	3024	1364
35°	1605	1012
45°	526	427
55°	160	152
65°	58	59
75°	19	20
85°	0	3
90°	0	



TEST NUMBER: P203309

CATALOG NUMBER: LD6B70D010TE EU6B60709040 6LBMH1

CANDELA DISTRIBUTION (FULL):

	0°
0°	4448.8
2.5°	4436.0
5°	4352.5
7.5°	4230.5
10°	4082.9
12.5°	3922.4
15°	3755.5
17.5°	3569.3
20°	3402.4
22.5°	3229.1
25°	3023.7
27.5°	2741.2
30°	2407.4
32.5°	2015.8
35°	1604.9
37.5°	1258.3
40°	956.5
42.5°	712.6
45°	526.4
47.5°	385.2
50°	282.5
52.5°	211.8
55°	160.5
57.5°	122.0
60°	96.3
62.5°	70.6
65°	57.8
67.5°	44.9
70°	32.1
72.5°	25.7
75°	19.3
77.5°	12.8
80°	6.4
82.5°	6.4
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)