

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P252853

Luminaire Tested: **LD6B70D010TE EU6B60709050 6LBBA1MW**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P252853
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-1712-453-2)
Test Lab: INNOVATION CENTER(G1)
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD6B70D010TE EU6B60709050 6LBBA1MW
Description: PORTFOLIO 6 INCH BAFFLE RECESSED DOWNLIGHT, WITH MATTE WHITE TRIM
Light Source: (1) HIGH LUMEN LED 90CRI / 5000K CCT
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 7859.0 lumens
Efficiency: N/A
Efficacy: 98.9 lumens/watt
Spacing Criteria (0/90/45): 1.03 / 1.03 / 1
Luminous Opening: Circular (Dia: 0.46' x H: 0')
CIE Type: Direct


Input Watts (W): 79.45
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P252853

CATALOG NUMBER: LD6B70D010TE EU6B60709050 6LBB A1MW

Luminous Intensity Polar Plot





TEST NUMBER: P252853

CATALOG NUMBER: LD6B70D010TE EU6B60709050 6LBBA1MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	111	107	104	101	108	105	102	99	101	98	96	97	95	93	94	92	90	88			
2	103	97	91	87	101	95	90	86	91	87	84	88	85	82	85	83	80	78			
3	96	87	81	76	94	86	80	75	83	78	74	81	76	72	78	74	71	69			
4	90	80	72	67	87	78	72	66	76	70	66	74	69	65	72	68	64	62			
5	84	73	65	60	82	72	65	60	70	64	59	68	63	58	66	62	58	56			
6	78	67	60	54	77	66	59	54	65	58	54	63	57	53	62	57	53	51			
7	74	62	55	49	72	61	54	49	60	53	49	59	53	49	57	52	48	47			
8	69	58	50	45	68	57	50	45	56	49	45	55	49	45	53	48	44	43			
9	65	54	46	42	64	53	46	42	52	46	41	51	45	41	50	45	41	39			
10	62	50	43	39	61	50	43	39	49	43	38	48	42	38	47	42	38	37			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	351667
5°	348439
10°	340762
15°	329943
20°	316618
25°	297226
30°	257203
35°	200257
40°	152208
45°	118652
50°	98411
55°	88322
60°	80416
65°	74207
70°	68174
75°	63169
80°	57107
85°	52249



TEST NUMBER: P252853

CATALOG NUMBER: LD6B70D010TE EU6B60709050 6LBBA1MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	502.2	6.4
10°-20°	1372.5	17.5
20°-30°	1869.3	23.8
30°-40°	1581.8	20.1
40°-50°	1014.7	12.9
50°-60°	698.3	8.9
60°-70°	477.0	6.1
70°-80°	265.4	3.4
80°-90°	77.7	1.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	3744.0	47.6
0°-40°	5325.8	67.8
0°-60°	7038.9	89.6
0°-90°	7859.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	7859.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	5390	
5°	5320	502
15°	4885	1373
25°	4129	1869
35°	2514	1582
45°	1286	1015
55°	776	698
65°	481	477
75°	251	265
85°	70	78
90°	0	



TEST NUMBER: P252853

CATALOG NUMBER: LD6B70D010TE EU6B60709050 6LBB1MW

CANDELA DISTRIBUTION (FULL):

	0°
0°	5390.3
2.5°	5369.8
5°	5320.5
7.5°	5242.4
10°	5143.8
12.5°	5020.6
15°	4885.0
17.5°	4728.9
20°	4560.4
22.5°	4371.4
25°	4129.0
27.5°	3800.4
30°	3414.2
32.5°	2970.4
35°	2514.4
37.5°	2115.9
40°	1787.2
42.5°	1511.9
45°	1286.0
47.5°	1109.3
50°	969.6
52.5°	862.8
55°	776.5
57.5°	694.3
60°	616.3
62.5°	546.4
65°	480.7
67.5°	415.0
70°	357.4
72.5°	299.9
75°	250.6
77.5°	201.3
80°	152.0
82.5°	110.9
85°	69.8
87.5°	28.8
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)