

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P205062

Luminaire Tested: **LD6B70D010TE EU6B60709050 6LBCSMMS1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P205062
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD6B70D010TE EU6B60709050 6LBCSMMS1
Description: PORTFOLIO 6 INCH SHALLOW RECESSED DOWNLIGHT
SHALLOW DISTRIBUTION WITH CAST MATTE METALLIC SILVER TRIM
SINGLE DRIVER D010TE
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 6353.1 lumens
Efficiency: N/A
Efficacy: 80.0 lumens/watt
Spacing Criteria (0/90/45): 1.16 / 1.16 / 1.27
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 79.45
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P205062

CATALOG NUMBER: LD6B70D010TE EU6B60709050 6LBCSMMS1

Luminous Intensity Polar Plot





TEST NUMBER: P205062

CATALOG NUMBER: LD6B70D010TE EU6B60709050 6LBCSMMS1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100	100	100	100
1	111	107	103	100	108	105	101	98	100	98	95	97	94	92	93	91	90	88	88	88	88
2	102	95	89	84	99	93	88	83	90	85	81	86	83	79	83	80	78	76	76	76	76
3	94	85	77	72	92	83	76	71	80	74	70	77	73	69	75	71	67	65	65	65	65
4	87	76	68	62	84	74	67	61	72	66	61	70	64	60	68	63	59	57	57	57	57
5	80	68	60	54	78	67	59	54	65	58	53	63	57	53	61	56	52	50	50	50	50
6	74	62	54	48	72	61	53	47	59	52	47	58	51	47	56	51	46	44	44	44	44
7	69	56	48	42	67	56	48	42	54	47	42	53	46	42	51	46	41	40	40	40	40
8	64	52	44	38	63	51	43	38	50	43	38	48	42	38	47	42	37	36	36	36	36
9	60	48	40	35	59	47	40	34	46	39	34	45	39	34	44	38	34	32	32	32	32
10	57	44	36	31	55	43	36	31	43	36	31	42	35	31	41	35	31	29	29	29	29

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P205062

CATALOG NUMBER: LD6B70D010TE EU6B60709050 6LBCSMMS1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	274.9	4.3
10°-20°	771.5	12.1
20°-30°	1126.8	17.7
30°-40°	1288.8	20.3
40°-50°	1238.6	19.5
50°-60°	956.5	15.1
60°-70°	533.9	8.4
70°-80°	155.4	2.4
80°-90°	6.7	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2173.2	34.2
0°-40°	3462.0	54.5
0°-60°	5657.1	89.0
0°-90°	6353.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	6353.1	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2918	
5°	2893	275
15°	2737	771
25°	2449	1127
35°	2063	1289
45°	1615	1239
55°	1072	956
65°	534	534
75°	136	155
85°	4	7
90°	0	



TEST NUMBER: P205062

CATALOG NUMBER: LD6B70D010TE EU6B60709050 6LBCSMMS1

CANDELA DISTRIBUTION (FULL):

0°	
0°	2917.5
2.5°	2917.5
5°	2892.8
7.5°	2880.5
10°	2839.4
12.5°	2790.1
15°	2736.7
17.5°	2683.3
20°	2605.2
22.5°	2543.5
25°	2449.0
27.5°	2354.5
30°	2260.0
32.5°	2165.5
35°	2062.8
37.5°	1960.0
40°	1840.9
42.5°	1734.0
45°	1614.9
47.5°	1479.3
50°	1351.9
52.5°	1212.2
55°	1072.5
57.5°	928.7
60°	793.1
62.5°	657.5
65°	534.2
67.5°	419.1
70°	312.3
72.5°	217.8
75°	135.6
77.5°	69.9
80°	24.7
82.5°	8.2
85°	4.1
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)