

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P204650

Luminaire Tested: **LD6B70D010TE EU6B60709050 6LBSMW1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P204650
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD6B70D010TE EU6B60709050 6LB5MW1
Description: PORTFOLIO 6 INCH SHALLOW RECESSED DOWNLIGHT
SHALLOW DISTRIBUTION WITH MATTE WHITE TRIM
SINGLE DRIVER D010TE
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 6708.9 lumens
Efficiency: N/A
Efficacy: 84.4 lumens/watt
Spacing Criteria (0/90/45): 1.24 / 1.24 / 1.34
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 79.45
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P204650

CATALOG NUMBER: LD6B70D010TE EU6B60709050 6LBSMW1

Luminous Intensity Polar Plot





TEST NUMBER: P204650

CATALOG NUMBER: LD6B70D010TE EU6B60709050 6LBSMW1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				20	
RC	80				70				50				30				10				0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0	
RCR																						
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100				100
1	110	106	102	99	107	104	100	97	99	97	94	96	93	91	92	90	88	86				86
2	101	93	87	82	98	92	86	81	88	83	79	85	81	77	82	79	76	74				74
3	93	83	75	69	90	81	74	69	78	72	67	76	70	66	73	69	65	63				63
4	85	74	65	59	83	72	65	59	70	63	58	68	62	57	66	61	56	54				54
5	78	66	58	51	76	65	57	51	63	56	51	61	55	50	59	54	49	47				47
6	73	60	51	45	71	59	51	45	57	50	44	55	49	44	54	48	44	42				42
7	67	54	46	40	66	54	46	40	52	45	40	51	44	39	49	43	39	37				37
8	63	50	41	36	61	49	41	36	48	41	35	46	40	35	45	39	35	33				33
9	59	46	38	32	57	45	37	32	44	37	32	43	36	32	42	36	32	30				30
10	55	42	34	29	54	42	34	29	41	34	29	40	33	29	39	33	29	27				27

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P204650

CATALOG NUMBER: LD6B70D010TE EU6B60709050 6LBSMW1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	256.1	3.8
10°-20°	730.0	10.9
20°-30°	1099.5	16.4
30°-40°	1308.3	19.5
40°-50°	1305.9	19.5
50°-60°	1062.0	15.8
60°-70°	653.4	9.7
70°-80°	253.1	3.8
80°-90°	40.6	0.6
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2085.6	31.1
0°-40°	3393.9	50.6
0°-60°	5761.8	85.9
0°-90°	6708.9	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	6708.9	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2703	
5°	2695	256
15°	2592	730
25°	2393	1099
35°	2095	1308
45°	1697	1306
55°	1188	1062
65°	656	653
75°	231	253
85°	32	41
90°	0	



TEST NUMBER: P204650

CATALOG NUMBER: LD6B70D010TE EU6B60709050 6LBSMW1

CANDELA DISTRIBUTION (FULL):

0°	
0°	2703.0
2.5°	2707.0
5°	2695.1
7.5°	2679.2
10°	2659.3
12.5°	2623.5
15°	2591.7
17.5°	2544.0
20°	2492.3
22.5°	2444.6
25°	2393.0
27.5°	2321.4
30°	2249.9
32.5°	2182.3
35°	2094.8
37.5°	1999.4
40°	1912.0
42.5°	1804.7
45°	1697.3
47.5°	1582.1
50°	1458.8
52.5°	1331.6
55°	1188.5
57.5°	1049.4
60°	914.3
62.5°	783.1
65°	655.9
67.5°	536.6
70°	425.3
72.5°	322.0
75°	230.6
77.5°	151.1
80°	91.4
82.5°	55.7
85°	31.8
87.5°	15.9
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)