

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P684893

Luminaire Tested: **LX6C20D010 EX6209030 6LBSLI**

Issue Date: 2/15/2022



Test Information

Test Method: LM-79-08
Report Number: P684893
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P205419)
Test Lab: INNOVATION CENTER
Issue Date: 2/15/2022
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LX6C20D010 EX6209030 6LBSLI
Description: 6 INCH 2000 LUMEN PORTFOLIO LED DOWNLIGHT WITH, 3000K, 90CRI LEDS
AND 6LBS TRIM WITH LI FINISH
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 2195.0 lumens
Efficiency: N/A
Efficacy: 100.7 lumens/watt
Spacing Criteria (0/90/45): 0.91 / 0.91 / 1.04
Luminous Opening: Circular (Dia: 0.5' x H: 0')
CIE Type: Direct

Input Watts (W): 21.8
Input Voltage (V):
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P684893

CATALOG NUMBER: LX6C20D010 EX6209030 6LBSLI

Luminous Intensity Polar Plot





TEST NUMBER: P684893

CATALOG NUMBER: LX6C20D010 EX6209030 6LBSLI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			100
1	111	107	104	101	109	105	102	99	101	99	96	97	95	93	94	92	91	89			89
2	103	96	91	86	100	94	89	85	91	87	83	88	84	81	85	82	79	77			77
3	95	86	79	74	93	85	78	73	82	76	72	79	75	71	77	73	70	68			68
4	88	78	70	64	86	77	69	64	74	68	63	72	67	62	70	65	62	60			60
5	82	71	63	57	80	70	62	57	67	61	56	66	60	55	64	59	55	53			53
6	76	64	56	51	74	63	56	51	62	55	50	60	54	50	59	53	49	47			47
7	71	59	51	46	70	58	51	45	57	50	45	55	49	45	54	49	45	43			43
8	67	54	47	41	65	54	46	41	52	46	41	51	45	41	50	45	41	39			39
9	63	50	43	38	61	50	43	38	49	42	38	48	42	37	47	41	37	36			36
10	59	47	40	35	58	46	39	35	45	39	35	45	39	34	44	38	34	33			33

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	75931
5°	75071
10°	71263
15°	65772
20°	60129
25°	54445
30°	49596
35°	45882
40°	42887
45°	39950
50°	36391
55°	31865
60°	26588
65°	20871
70°	14570
75°	7900
80°	1484
85°	0



TEST NUMBER: P684893

CATALOG NUMBER: LX6C20D010 EX6209030 6LBSLI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	127.6	5.8
10°-20°	324.9	14.8
20°-30°	414.4	18.9
30°-40°	429.7	19.6
40°-50°	396.0	18.0
50°-60°	297.8	13.6
60°-70°	160.8	7.3
70°-80°	43.1	2.0
80°-90°	0.6	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	866.9	39.5
0°-40°	1296.7	59.1
0°-60°	1990.4	90.7
0°-90°	2195.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2195.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1385	
5°	1364	128
15°	1159	325
25°	900	414
35°	686	430
45°	515	396
55°	333	298
65°	161	161
75°	37	43
85°	0	1
90°	0	



TEST NUMBER: P684893

CATALOG NUMBER: LX6C20D010 EX6209030 6LBSLI

CANDELA DISTRIBUTION (FULL):

	0°
0°	1385.1
2.5°	1380.5
5°	1364.2
7.5°	1333.8
10°	1280.2
12.5°	1226.6
15°	1158.9
17.5°	1096.0
20°	1030.7
22.5°	963.1
25°	900.1
27.5°	839.5
30°	783.5
32.5°	732.2
35°	685.6
37.5°	641.3
40°	599.3
42.5°	555.0
45°	515.3
47.5°	471.1
50°	426.7
52.5°	380.1
55°	333.4
57.5°	286.8
60°	242.5
62.5°	200.5
65°	160.9
67.5°	123.6
70°	90.9
72.5°	63.0
75°	37.3
77.5°	16.3
80°	4.7
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180°







(END OF REPORT)